



Expandable Sleeving consists of flexible, flame-retardant woven polyester monofilament that met RoHS standard. The sleeving is able to expand up to 3 times its normal size and is used for bundling and protection of electrical cables and hose in power-supply ,communication and automobile sectors.

- Material: polyester (PET) ,free from halogen,low smoke,flame-retardant.
- Temperature range : -30°C ---- 125°C
- Flammability : self-extinguishing meets VW-1 of UL
- Standard colours:black,gray,white,red,green,blue,yellow,purple,pink, orange,nacarat.
- Melting point: 230°C ±5
- Does not trap heat or humidity
- Rot-free
- Self-fitting over many shapes and sizes
- Self-extinguishing when used to encase typical non-flammable wires or cables
- Fray resistant
- Approval : UL,SGS,RoHS



E303531

No.2052747/EC

Part Number	SIZE		Material	Expandable Range		Temperature Range		Standard Packing
	mm	inch		mm	inch			
JDD-PES-003	3MM	1/8"	polyester	2.4--6.4	3/32"--1/4"	-94° F to 257° F	-70° C to 125° C	1000M/Roll 3280ft/Roll
JDD-PES-006	6MM	1/4"	polyester	3.2--11.1	1/8"--7/16"	-94° F to 257° F	-70° C to 125° C	500M/Roll 1640ft/Roll
JDD-PES-008	8mm	5/16"	polyester	6.4--12.7	1/4"--1/2"	-94° F to 257° F	-70° C to 125° C	350M/Roll 1148ft/Roll
JDD-PES-010	10mm	3/8"	polyester	4.8--15.9	3/16"--5/8"	-94° F to 257° F	-70° C to 125° C	350M/Roll 1148ft/Roll
JDD-PES-012	12MM	1/2"	polyester	6.4--19.1	1/4"--3/4"	-94° F to 257° F	-70° C to 125° C	300M/Roll 984ft/Roll
JDD-PES-016	16MM	5/8"	polyester	9.5--25.4	3/8"--1"	-94° F to 257° F	-70° C to 125° C	250M/Roll 820ft/Roll
JDD-PES-019	19MM	3/4"	polyester	12.7--31.8	1/2"--1-1/4"	-94° F to 257° F	-70° C to 125° C	300M/Roll 984ft/Roll
JDD-PES-025	25MM	1"	polyester	15.9--38.1	5/8"--1-1/2"	-94° F to 257° F	-70° C to 125° C	200M/Roll 656ft/Roll
JDD-PES-032	32MM	1-1/4"	polyester	19.1--44.5	3/4"--1-3/4"	-94° F to 257° F	-70° C to 125° C	150M/Roll 492ft/Roll
JDD-PES-038	38MM	1-1/2"	polyester	25.4--63.5	1"--2-1/2"	-94° F to 257° F	-70° C to 125° C	100M/Roll 328ft/Roll
JDD-PES-045	45MM	1-3/4"	polyester	31.8--69.9	1-1/4"--2-3/4"	-94° F to 257° F	-70° C to 125° C	100M/Roll 328ft/Roll
JDD-PES-051	51MM	2"	polyester	38.1--88.9	1-1/2"--3-1/2"	-94° F to 257° F	-70° C to 125° C	100M/Roll 328ft/Roll
JDD-PES-064	64MM	2-1/2"	polyester	44.5--114.3	1-3/4"--4-1/2"	-94° F to 257° F	-70° C to 125° C	100M/Roll 328ft/Roll
JDD-PES-076	76MM	3"	polyester	63.5--120.7	2-1/2"--4-3/4"	-94° F to 257° F	-70° C to 125° C	100M/Roll 328ft/Roll