















厚普光电有限公司  
**Hope LED Opto-electric Co.,Ltd.**

Add: No.3 Qiaonan New Village, Fuyong, Bao'an District, Shenzhen, Guangdong Province, PRC  
 Web: [www.hopeled.com](http://www.hopeled.com) [www.hope-ledlight.com](http://www.hope-ledlight.com)  
 Email: [sales@hopeled.com](mailto:sales@hopeled.com); [happylynn211@hotmail.com](mailto:happylynn211@hotmail.com)



**COB LED Ceiling Light (3-year Warranty)**

No.	Model No.	Pictures	Size (mm)	Hole Size (mm)	Electrical Data	LED	Unit Price / USD (with 2 types chips)		Remark	
							Bridgelux	Other chip		
1	HP-NDL-1WA		D50xH40	∅ 45	Input 90-260v AC; 350mA	1pc high power 1w LED; Bridgelux 45mil or KWE 35mil	<b>Blank</b>	KWE LED	LED Friend driver	
2	HP-NDL-1WB	 <a href="http://www.hopeled.com">www.hopeled.com</a>	D60xL60xH40	∅ 45	Input 90-260v AC; 350mA	1pc high power 1w LED; Bridgelux 45mil or KWE 35mil		KWE LED		
3	HP-NDL-5WA		D85xH75	∅ 75	Input 90-260v AC; 350mA	1pc 5w COB Bridgelux LED; 10pcs 0.5W 24mil Bridgelux chip		Blank		
4	HP-NDL-5WB	 <a href="http://www.hopeled.com">www.hopeled.com</a>	D92xL92xH75	∅ 80	Input 90-260v AC; 350mA	1pc COB Bridgelux LED; 10pcs 0.5W 24mil Bridgelux chip		Blank	Meanwell driver	
5	HP-NDL-10WA		D120xH90	∅ 105	Input 90-260v AC; 350mA	1pc 10w COB Bridgelux LED; 10pcs 1W Bridgelux chip				
6	HP-NDL-15WA	 <a href="http://www.hopeled.com">www.hopeled.com</a>	D114xH100mm	∅ 95	Input 90-260v AC; 350-440mA	1pc 15W Sharp COB LED		Sharp COB LED, LED Friend driver or Meanwell Driver		
7	HP-NDL-20WA		D150xH195mm	∅ 140		1pc COB Bridgelux LED; 20pcs 1W Bridgelux chip; two types PCB <b>Meanwell driver</b>		Bridgelux 20w	Bridgelux 20w	see difference of the LED as follows
										

No.	Model No.	Pictures	Size (mm)	Hole Size (mm)	Electrical Data	LED	Unit Price / USD (with 2 types chips)		Remark
							Bridgelux	Epistar	
8	HP-NDL-4WA		D85xH67mm	∅ 70	Input 90-260v AC; 300mA	1pc high power 1w Bridgelux 45mil or Epistar 35mil COB LED	<b>Blank</b>	LED Friend driver	
9	HP-NDL-7WA		D90xH77mm	∅ 73	Input 90-260v AC; 300mA	1pc high power 1w Bridgelux 45mil or Epistar 35mil COB LED			
10	HP-NDL-10WB		D100xH77mm	∅ 82	Input 90-260v AC; 300mA	1pc high power 1w Bridgelux 45mil or Epistar 35mil COB LED		Meanwell driver	
11	HP-NDL-15WB		D120xH87mm	∅ 100	Input 90-260v AC; 300mA	1pc high power 1w Bridgelux 45mil or Epistar 35mil COB LED			

**Remark:**

1. **MOQ for Sharp type: 50PCS**
2. **3-year warranty for Bridgelux / Sharp type; while 2-year warranty for Epistar!**
3. **Price is fluctuated if exchange rate 1USD to RMB is lower than 6.2**
4. **Price quoted is EXW.**