

*** Quotation ***

Joney Technology Co.,Ltd

Wireless Control Panel/Detector/Accessories





MSN:sherry10201@hotmail.com

Email:mail@joneytech.com/sales@joneytech.com

Skype:sherry102011

Tel:86-755-86098525











CE, RoHS APPROVAL


PICTURE	MODEL	Description
	ST-II	<ul style="list-style-type: none"> ◎ LCD display, Voice indication for operation ◎ 8 wired zones + 32 wireless zones, 8 electric appliance control , built-in door chime
	ST-II Whole set	<ul style="list-style-type: none"> ◎ Remote programming via phone, timing arm/disarm, 10s address record ◎Wireless devices status checking ◎Telephone lint cut alarm, can send out alarm via neighbor's panel, zone not ready remind ◎Built-in treble siren, 10pcs rechargeable battery unit
Whole set	ST-II(GSM)	With GSM function
NEW	ST-II(TCP/IP)	With TCP/IP function
	ST-III (HOT)	<ul style="list-style-type: none"> ◎ LCD display, Voice indication for operation ◎ 8 wired zones + 32 wireless zones, 8 electric appliance control , built-in door chime
	ST-III Whole set	<ul style="list-style-type: none"> ◎ Remote programming via phone, timing arm/disarm, 10s address record ◎Wireless devices status checking ◎Telephone lint cut alarm, can send out alarm via neighbor's panel, zone not ready remind ◎Built-in treble siren, 10pcs rechargeable battery unit
Whole set	ST-III GSM	With GSM function

NEW	ST-III(TCP/IP)	With TCP/IP function			
	ST-IV whole set(HOT)	<ul style="list-style-type: none"> ◎ Large LCD display ◎ Voice indication for operation ◎ 8 wired zones+32 wireless zones, 8 multi-function remote controllers ◎ Remote control by telephone,10s address recording, arm/disarm timely and freely 			
	ST-IV whole set(HOT) with GSM Module	<ul style="list-style-type: none"> ◎ Support GSM ◎ Large LCD display ◎ Voice indication for operation ◎ 8 wired zones+32 wireless zones, 8 multi-function remote controllers ◎ Remote control by telephone,10s address recording, arm/disarm timely and freely 			
	ST-V(HOT) Whole kit	<ul style="list-style-type: none"> ◎ LCD display, Voice indication for operation ◎ 8 wired zones + 32 wireless zones, 210 BUS zones 			
	ST-V Whole set(with GSM function)	<ul style="list-style-type: none"> ◎ 4 subsystem, bidirectional wireless communication ◎ 32 electric appliance control ◎ GSM module, SMS alarm, build-in TCP/IP module optional ◎ Wired/wireless zones status real-time checking ◎ 4 groups programmable timing arm/disarm; remote arm/disarm, listen-in 			
	FC-300 (HOT)	<ul style="list-style-type: none"> ◎ LCD display ◎ Voice indication for operation ◎ 8 wired zones+32 wireless zones, 8 multi-function remote controllers ◎ 4 groups programmable timing arm/disarm; remote arm/disarm, listen-in ◎ 10 sec. alarm address record. 			
	FT-89R (HOT) Outdoor use	<ul style="list-style-type: none"> ◎ Detection method: 2 group dual PIR+ dual MW ◎ Detection distance: 9m/12m/18m ◎ Detection angle: 30° /90° /120° 			
	DDP-968 (Door&window Guard)	<ul style="list-style-type: none"> ◎ Detection method: Dual IR+MW ◎ Detection range: 3m@25℃ ◎ Detection angle: 20° ◎ Pet-immunity: 20KG 			

	MC-760R (Wireless PIR detector)	<ul style="list-style-type: none"> ◎ Sensor: Low-noise high sensitivity Dual pyroelectric optical sensor ◎ Detection distance: 12m@25°C ◎ Detection angle: 110° 			
	DM-7380R (Ceiling mount)	<ul style="list-style-type: none"> ◎ Detection method: Dual PIR ◎ Detection distance: Diameter 10m@25°C ◎ Detection angle: 270° 			
	PE-81R	<ul style="list-style-type: none"> ◎ Detection method: Dual PIR ◎ Detection distance: 12m@25°C ◎ Detection angle: 20° 			
	MC-335R (Wireless PIR detector)	<ul style="list-style-type: none"> ◎ Detection method: Dual PIR ◎ Detection distance: 12m@25°C ◎ Detection angle: 20° 			
	DT-335R (Wireless PIR+MW)	<ul style="list-style-type: none"> ◎ Detection method: Dual PIR+MW ◎ Detection distance: 12m@25°C ◎ Detection angle: 20° 			
	MC-355R (Wireless PIR detector)	<ul style="list-style-type: none"> ◎ Sensor: Low-noise high sensitivity Dual pyroelectric optical sensor ◎ Detection distance: 12m@25°C ◎ Detection angle: 110° 			
	MC-8250R (Wireless digital PIR detector)	<ul style="list-style-type: none"> ◎ Detection method: Dual PIR ◎ Detection distance: 12m@25°C ◎ Detection angle: 110° 			
	MC-8880R (Wireless digital dual infrared detector) come out soon	<ul style="list-style-type: none"> ◎ Detection method: Dual PIR ◎ Detection distance: 18m@25°C ◎ Detection angle: 110° 			
	MC-235R (Wireless PIR detector)	<ul style="list-style-type: none"> ◎ Sensor: Low-noise high sensitivity Dual pyroelectric optical sensor ◎ Detection distance: 12m@25°C ◎ Detection angle: 110° 			
	DT-55R (Wireless PIR+MW)	<ul style="list-style-type: none"> ◎ Detection method: Dual PIR & MW ◎ Detection distance: 12m@25°C ◎ Detection angle: 110° 			
	MC-55R (Wireless digital PIR detector)	<ul style="list-style-type: none"> ◎ Sensor: Low-noise high sensitivity dual Pyroelectric infrared sensor ◎ Detection distance: 12m@25°C ◎ Detection angle: 110° 			
	MD-448R (Wireless curtain style detector)	<ul style="list-style-type: none"> ◎ Detection method: Dual PIR ◎ Detection distance: 6m@25°C ◎ Detection angle: 20° 			

	MD-204R (Wireless siren)	<ul style="list-style-type: none"> ◎ With tamper function, self-checking and send a status report periodically ◎ Beautiful out looking, round voice, fit for installation of veranda, window. 			
	MD-314R (Wireless siren with flashing light)	<ul style="list-style-type: none"> ◎ DC Power: DC12V (Built-in rechargeable battery: 12V/500mA) ◎ Remote distance > 100 m 			
	MD-334R (Wireless High-power dual-tone siren with light)	<ul style="list-style-type: none"> ◎ Double flashing light, built-in dual-tweeter ◎ Two-way communication with control panel ◎ Working power: 12VDC@ 100 μ A 			
	MD-324R (Solar battery wireless flash siren)	<ul style="list-style-type: none"> ◎ Solar powered: polycrystalline silicon solar cell ◎ Built-in rechargeable battery 6V/4Ah ◎ Wireless receiving sensitivity ≥104dB ◎ Emitting power: 14 ± 1dB 			
	MD-2000R (Wireless gas detector)	Wireless signal output, wired and wireless compatible			
	MD2100R (Wireless smoke detector)	Independent / Networking / Wireless Output (optional)			
	MD-209R (Wireless door sensor with panic button)	<ul style="list-style-type: none"> ◎ Current consumption Static state ≤5 μ A Emitting current ≤15mA ◎ Emitting frequency 433MHz/868MHz ◎ Wireless emitting distance (Internal antenna): 200m 			
	MD-210R (Wireless door sensor)	<ul style="list-style-type: none"> ◎ Current consumption Static state ≤5 μ A Emitting current ≤15mA ◎ Emitting frequency 433MHz/868MHz ◎ Wireless emitting distance (Internal antenna): 200m 			
	MD-212R (Wireless roll gate magnetic detector)	<ul style="list-style-type: none"> ◎ Effective distance ≤60 mm ◎ Low voltage alarm: Low voltage light will flash when battery voltage is below 8V. ◎ Emitting distance 200m (Direct distance without obstacles) 			
	MD-219R (Wireless door sensor)	<ul style="list-style-type: none"> ◎ Current consumption Static state ≤5 μ A Emitting current ≤15mA ◎ Emitting frequency 433MHz/868MHz ◎ Wireless emitting distance (Internal antenna): 200m 			

	PB-433R (Wireless Slide Remote Control)	<ul style="list-style-type: none"> ◎ 4 pressbutton mini wireless remote controller ◎ Metal surface ◎ Metal fastener 			
	PB-403R (Remote controller)	<ul style="list-style-type: none"> ◎ 6 pressbutton mini wireless remote controller ◎ With 2 appliance control button ◎ Metal fastener 			
	PL-206 (Wireless Electronic Switch 2-line)	<ul style="list-style-type: none"> ◎ Match with FOCUS series control panel ◎ Real time status report, dual-way wireless communication, status check ◎ Hand control/remote control 			
	PL-208 (Wireless Electronic Switch 3-line)	<ul style="list-style-type: none"> ◎ Max. load: 220V AC/600W ◎ Signal emitting frequency : 433 /868MHZ ± 50KHZ ◎ Emitting power: 12dB ◎ Receiving sensitivity: -108dB 			
	PB-200R (Wireless embedded emergency button)	<ul style="list-style-type: none"> ◎ Structure 86 electronical box ◎ Surface mount ◎ Timing status report ◎ ABS flame retardant housing 			
	PB-201R (Wireless hanging style emergency button)	<ul style="list-style-type: none"> ◎ Timing status report ◎ Waterproof IP55 ◎ ABS flame retardant housing 			
	PB-301R (Wireless repeater)	<ul style="list-style-type: none"> ◎ Wireless transmitting distance:1-10km(in broad area), 1-3km(with barrier area) 			
	PB-303R (Wireless to Wired converter)	<ul style="list-style-type: none"> ◎ 16 open-collector output ◎ Max. enroll 4 sensors each zone ◎ Rechargeable battery(optional) 			
	PB-305R (Wireless to BUS converter)	<ul style="list-style-type: none"> ◎ With CAN BUS input interface, support N.O./N.C., used to connect BUS alarm equipment into users' wireless network alarm system. 			
	PB-506R (Wireless doorbell)	<ul style="list-style-type: none"> ◎ Structure 86 electronical box ◎ Surface mount ◎ Timing status report ◎ ABS flame retardant housing 			

	PB-500R (LCD wireless keypad)	<ul style="list-style-type: none"> ◎ LCD display ◎ Intelligent self-locking (will trigger alarm if continuous 5 times wrong password input) ◎ Send a status report periodically ◎ Two-way wireless communication 			
-----------------------------------------------------------------------------------	-----------------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--	--	--

Terms and Conditions

Prices above are based on FOB SHENZHEN.

Delivery: 5 - 30 days after order confirmed

Payment: Overseas - By T/T

Sample: Available against advance payment and your courier account details provided

Sample Charges: Both sample costs and courier freight charges are on buyer's account.

Certificates: CE, 3C & ISO9001:2000 Certificates available.

Remarks: Prices excluding special packing and requirement.

Price, Terms, Conditions and Specifications are subject to our final confirmation.