

VHP PUMP 技术参数

TECHNICAL PARAMETER (技术参数)		SX245	SX222	LC17
General information 常规资料	Nominal power(KW/Hp)额定功率	45/60	22/30	7.5/10
	Unladen weight(kg)净重	1100	1000	300
	Length(mm)长度	1500	1500	1000
	Width (mm)宽	900	900	700
	Height(mm) 高	1450	1450	1000
Hydraulic system 高压水系统	Tank capacity (l)油槽容量	200	200	60
	Recommended oil 推荐油型	ISO 32	ISO 32	ISO 68
	Pump flow rate (l/mn)流量	120	60	25
	Working pressure (bar)工作压力	190(250 for the SX 245P)	190	190
Electrical supply 电气部分	Voltage (VAC)电压	400	400	400
	Current(A):Absorbed/protection 电流 (A): 工作/峰值	81/100	42/63	15/20
	Frequency (HZ)频率	50/60	50/60	50
Water cutting 水切割	Water cutting supply minimum flow-rate 水切割最低流量	10 l/mn at 3 bars	5 l/mn at 3 bars	2 l/mn at bars
	Maximum flow rate (l/mn) 最大流量	4.6(3.6 for the SX245p)	2.6	0.8
	Maximum working pressure (bar) 最大工作压力	4000(5000 bars for the SX245P)	4000	4000
	Low pressure inlet connection 低压进水口接口	Ø19	Ø19	Ø19
	VHP pressure outlet connection 高压出水口接口	1/4	1/4	1/4
Lubrication 润滑	Voltage(V)电压	230	230	400 or 230
	Amperage (A)电流	1.3	1.3	0.4or 1.3
	Working pressure (bar)工作压力	15	15	12or 15
Air/oil exchanger (option) 空气/油交换器 (可选)	Motor power (kw)发动机功率	2×(0.45)+0.75	0.45	0.12
	Voltage (V)电压	400	400	400
	Amperage (A)电流	2×(0.84)+1.91	0.84	0.26
	Frequency (HZ)频率	50/60	50/60	50/60
Water/oil exchanger 水/油交换器 (散热器)	Water cooling supply minimum flow Rate 水冷却最低流量	15 l/mn at 10 度	10l/mn at 10 度	10 l/mn at 10 度
Sound level with air cooling 噪音音量	1 m distance from the pump (dBA-Leq)距泵 1 米距离测试	75	78	75
Water filters 水过滤器	2 low pressure filter 双面低压过滤器	5 p and 1p	5 p and 1p	5 p and 1p