



# GUANGZHOU JINGLE TRADE CO.,LTD

CELL: 86 13418195777  
Email: hejanxin@vip.163.com

OFFICE TELL: 86 02083020912  
Web: www.jinglecn.com

<b>Bulletproof Standard</b>							
<b>Ministry of National Public Security GA141-2001</b>							
Bulletproof level	category of firearm		category of ammunition		Muzzle Velocity M/S		
1	7.62mm pistol in 1964 and 1977		7.62mm pistol bullet in 1964		300-320		
2	7.62mm pistol in 1954		7.62mm pistol bullet in 1951		420-450		
3	7.62mm light submachine gun in 1979		7.62mm pistol bullet in 1951		480-515		
4	7.62mm pistol in 1954		7.62mm/B pistol bullet in 1951		420-450		
5	7.62mm light submachine gun in 1979		7.62mm/B pistol bullet in 1951		480-515		
6	7.60mm semiautomatic rifle in 1956		7.62mm general bullet in 1956		710-735		
<b>Ministry of National Public Security GA293-2001</b>							
Bulletproof level	Shooting condition					Muzzle Velocity (m/s)	
	category of firearm	category of ammunition	shooting Angle(0°) (No more than)	shooting Distance M (no more than)			
I	64 or 77 pattern 7.62mm pistol	64or 7.62mm ammunition (lead core)	5	5	300-320		
II	54 pattern 7.62mm pistol	51 pattern 7.62mm ammunition(lead core)	5	5	420-450		
REMARK ©: The impacting shell is a circle centred by the impact centre and radial by 30mm, the distance between the impacting shell and the edge of the helmet should not be less than 50mm, the distance between the impacting shells should not be less than 50mm.							
<b>NIJ0101.04 Bulletproof standard of U.S.Department Justice</b>							
bulletproof level	Times of Test	Category of Bullets	Bullets Weight (g/rg)	Muzzle Velocity	Shootin g Distanc	Availa ble Shots	BFS Max Deepth
				(±30ft/s) (m/s/ft/s)			
I	1	22caliber LRLR	2.6/40	329/1080	5	6	44mm/1.73in
	2	80 ACP FMJ R	6.2/95	322/1055	5	6	44mm/1.73in
IIA	1	9mm FMJ RN	8.0/124	341/1120	5	6	44mm/1.73in
	2	40 S\$W FMJ	11.7/180	322/1055	5	6	44mm/1.73in
II	1	9mm FMJ RN	8.0/124	367/1205	5	6	44mm/1.73in
	2	357 Mag JSP	10.2/158	436/1430	5	6	44mm/1.73in
IIIA	1	9mm FMJ RN	8.2/124	436/1430	5	6	44mm/1.73in
	2	44 mAG SJHPP	15.6/240	436/1430	5	6	44mm/1.73in
III	1	52mm NATO F	9.6/148	847/2780	15	6	44mm/1.73in
IV	1	30caliber M2 A	10.8/166	878/2880	15	1	44mm/1.73in
Special	*	*	*	*	*	*	44mm/1.73in
REMARKS ©: AP,Armor Piercing; FMJ,Full Metal Jacket; JSP,Jacketed Soft(Point); RN,Round Nose; SJHP,Aemi-Jacketed Hollow Point; SWC,Semi Wad Cutter.							