

# ZGB2 系列信号避雷器

TEL: 028-88065610

成都领世科技有限责任公司 销售电话: 028-88065610 13666246696 传真: 86313805

序号	型号	原型号	接口	被保护脚	工作电压 (V)	传输速率 (bit/s)	插入损耗 (dB) ≤	通流容量 8/20μs (kA)	限制电压 10/700μs (V) ≤	外形尺寸 L×B×H (mm)	质量 (g)	用途	备注	序号	
1	ZGB235C3-12	ZGB235C-3	DB25 针/孔	2, 3, 7	12	20k	0.5	1.5	40	114×64×25	220	保护标准 RS232 接口、DTE、DCE 设备、机房内相关设备等	可根据用户提供的脚位数、接口阴阳定做, 三线以下的单价均为¥480, 三线以上每增加 1 线增加¥90。	1	
2	ZGB235C9-12	ZGB235C-9		1-8, 20						2					
3	ZGB235C11-12	ZGB235C-11		1-8, 15, 17, 20						3					
4	ZGB235C10-12	ZGB235C-10X		1-8, 20, 22						4					
5	ZGB235D9-12A	ZGB235D-9X	DB9 针/孔	1-9	5	20k	0.1	L/SG≤24 SG/E≤200	64×54×16	50	5				
6	ZGB235D9-12	ZGB235D-9							64×34×16	30	6				
7	ZGB235D4-5	ZGB235K-2	DB9 孔/针	1, 2; 3, 4	6	1M	0.5	1.5	40	114×44×25	180			保护 422/485 接口、LAN 网、工控系统	7
8	ZGB235D3-6	ZGB235J		4, 5, 9					25	84×54×25	110				8
9	ZGB235G8-12	ZGB235G-9	DB15	2, 9; 3, 10; 5, 12; 13	12	1	40	74×44×25	90	保护收发器、AUI 端口	9				
10	ZGB235F-2		RJ45	1, 2; 3, 6	5	10M	L/L 0.4; SE/E 2.5	8/20μs 300A 40	40	69×25×25	85	保护集线器、网卡、网络交换机等网络设备、	10BaseT	10	
11	ZGB235F4-5	ZGB235F-5		1, 2; 3, 6; 4, 5; 7, 8						113×45×25	180			11	
12	ZGB210F10-5	ZGB210A		1, 2, 3, 6						100M	251×100×46		1380	12	
13	ZGB210F16-5	ZGB210B									400×100×44		1730	13	
14	ZGB210F24-5	ZGB210C									483×100×44		2500	14	
15	ZGB235F-3										100×25×25		100	100BaseT	15
16	ZGB210F10-5H										251×100×46		1380	分别是 ZGB235F-3 的 10、16、24 组合	16
17	ZGB210F16-5H										400×100×44		1730		17
18	ZGB210F24-5H										483×100×44		2500		18
19	ZGB235F-12	ZGB235H-2	4, 5	12	64K	0.5	3	40	79×25×25	100	保护 DDN 专线、Modem			19	
20	ZGB235F4-12	ZGB235H-9	1, 2, 3, 4; 5, 6; 7, 8						90×64×25	150				20	
21	ZGB235F-110	ZGB235H-3	4, 5						110	300				79×25×25	100
22	ZGB235H-12	ZGB235H	RJ11	3, 4	12	64K	0.5	3	40	69×25×25	90		保护 DDN 专线、Modem		22
23	ZGB208H10-12	ZGB208-2A							217×102×42	750	23				
24	ZGB208H20-12	ZGB208-2							368×110×48	1200	24				
25	ZGB235H-110	ZGB235H-1							300	69×25×25	90	保护拨号线、Modem, PSTN, FAX, 语音卡等设备			25

## ZGB2 系列信号避雷器

TEL: 028-88065610

序号	型号	原型号	接口	被保护脚	工作电压 (V)	传输速率 (bit/s)	插入损耗 (dB) ≤	通流容量 8/20μs (kA)	限制电压 10/700μs (V) ≤	外形尺寸 L×B×H (mm)	质量 (g)	用途	备注	序号						
26	ZGB208H10-110	ZGB208-3A	RJ11	3, 4	110	64K			300	217×102×42	750	保护拨号线、Modem PSTN, FAX, 语音卡等设备		26						
27	ZGB208H20-110	ZGB208-3								368×110×48	1200			27						
28	ZGB235J-5	ZGB235K-1	接线端子	一对线	5	20K			25	64×44×25	80	工业控制互联网络、422/485 接口气		28						
29	ZGB235J2-5	ZGB235K		二对线						84×44×25	110			29						
30	ZGB235J-6			一对线	6	2M			20	81×25×25	10	RS422/485, PCM, Ethcrnet, 10BaseT		30						
31	ZGB235J2-6			二对线						81×56×25	105			31						
32	ZGB235J-12			一对线	12				40	81×25×25	70	专线、RS232 通信设备、Modem		32						
33	ZGB235J2-12			二对线						81×56×25	105			33						
34	ZGB235J-24			一对线	24				60	81×25×25	70	专线、自动控制和仪表线路、数据线		34						
35	ZGB235J2-24			二对线						81×56×25	105			35						
36	ZGB235J-48			一对线	48				90	81×25×25	70	专线、通讯设备		36						
37	ZGB235J2-48			二对线						81×56×25	105			37						
38	ZGB235J-110			一对线	110				300	81×25×25	70	电话设备、传真机		38						
39	ZGB235J2-110			二对线						81×56×25	105			39						
40	ZGB235J-130M			一对线	130	1M				170×120×90	680	密封型 PHS 基站专用		40						
41	ZGB235J2-130M	ZGB235J2-130H		二对线										41						
42	ZGB235N-1		N	同轴型	标称阻抗: 50Ω	5			1KV/μS: 20	95×25×25	125	粗缆		42						
43	ZGB235B-2	ZGB238A	BNC							标称阻抗: 75Ω	24	10M					78×25×25	80	细缆	43
44	ZGB235B-4	ZGB238A1/A2																	保护摄像头、矩阵控制器等监控设备	44
45	ZGB235B-5																		1KV/μS: 50	45
46	ZGB236X-24																		X-14	按用户要求
47	ZGB236J-24		接线端子	一对线	12			40	69×44×45	80	保护电流环中的传感器、二次表	电流 4-20mA	47							
48	ZGB236J-12											电 流 0-10mA	48							
49	ZGB236J4-12											保护摄像头控制系统	49							
50	ZGB236D-5	ZGB237	DB9	1, 2, 3,	5	2M		25	110×44×25	150	专用信号		50							