



BP系列子弹型摄像机 BP Series Waterproof Bullet Style Camera



Features

- Sony Hi-Res. Super HAD CCD Sensor
- 550TV Lines of Horizontal Resolution
- AES, AGC, AWB
- High Sensitivity
- Minimum illumination of 0.5 Lux Built-in
- Built-in Fixed Lens
- Weatherproof
- Low Smear
- Strong Back Light Compensation
- DC12V Input
- Low Power Consumption

SPECIFICATIONS 规格

Model No.	型号	BP-238PH	BP-242PH	BP-248PH	BP-240PS	BP-242PS	BP-248PS	BP-255PS	BP-242PSX	BP-248PSX
Image Sensor	图像传感器	Sharp Color CCD			Sony Super HAD CCD				Sony Exview HAD CCD	
Signal System	信号系统	PAL / NTSC								
CCD Size	CCD 尺寸图	1/4"	1/3"	1/3"	1/4"	1/3"	1/3"	1/3"	1/3"	1/3"
Effective Pixels	有效像素	PAL: 512(H)x582(V) NTSC: 512(H)x492(V)			PAL: 752(H)x582(V) NTSC: 768(H)x494(V)					
Horizontal Resolution	水平清晰度	380TV Lines	420TV Lines	480TV Lines	400TV Lines	420TV Lines	480TV Lines	550TV Lines	420TV Lines	480TV Lines
Sync. System	同步方式	Internal								
Electronic Shutter	电子快门	AutoPAL: 1/50~1/100,000(sec.) NTSC: 1/60~1/110,000(sec.)								
Gamma Characteristic	γ 特性	0.45								
White Balance	白平衡	AUTO								
SN Ratio	信噪比	More than 48dB(AGC OFF)								
Lens	可配镜头	3.6 mm Board Lens (2.9mm, 4mm, 8mm optional)								
Minimum Illumination	最低照度	1.0Lux/F2.0	0.8Lux/F2.0	1.0Lux/F2.0	0.8Lux/F2.0	0.5Lux/F2.0	0.8Lux/F2.0	0.8Lux/F2.0	0.01Lux/F2.0	0.05Lux/F2.0
Size	产品尺寸	φ 23x 65mm			φ 23x 80mm					
Back Light Compensation	背光补偿	AUTO								
Gain Control	增益控制	AUTO								
Video Output	视频输出	1.0Vp-p 75Ω BNC or RCA								
Power Requirement	所需电源	DC12V ± 10%								
Power Consumption	功率消耗	90 mA	100 mA	120 mA	120 mA	120 mA	150 mA	150 mA	150 mA	160 mA
Operating Temperature	工作温度	-10°C ~ +50°C (14°F ~ 122°F)								

DIMENSIONS 尺寸示图

