



DC12V / AC24V 双电源彩色摄像机 DC12V / AC24V Dual Voltage Box Style Camera



Features

- Sony Hi-Res. Super HAD CCD Sensor
- Ultra High Resolution 550TV Lines or 600TV Lines
- AES, AGC, AWB, AI
- High Sensitivity
- Minimum illumination of 0.5 Lux
- DC12V / AC24V Dual Voltage
- With Line Lock Function
- Low Smear
- Strong Back Light Compensation
- Low Power Consumption

SPECIFICATIONS 规格

Model No.	型号	PP-242PS	PP-248PS	PP-255PS	PP-260PS
Image Sensor	图像传感器	Sony SuperHAD CCD			Sony Exview HAD CCD
Signal System	信号系统	PAL / NTSC			
CCD Size	CCD 尺寸	1/3"	1/3"	1/3"	1/2"
Effective Pixels	有效像素	PAL:752(H)x582(V)		NTSC:768(H)x494(V)	
Horizontal Resolution	水平清晰度	420TV Lines	480TV Lines	550TV Lines	600TV Lines
Sync System	同步方式	Internal	Internal / External With Line Lock		
Electronic Shutter	电子快门	Auto:PAL: 1/50~1/100,000(sec.) NTSC:1/60~1/110,000(sec.)			
Auto Iris Lens	自动光圈镜头	DC / Video			
Gamma Characteristic	γ特性	0.45			
White Balance	白平衡	Auto Tracking White Balance			
S/N Ratio	信噪比	More than 48dB(AGC OFF)			
Lens Mount	可配镜头	C or CS mount adjustable			
Minimum Illumination	最低照度	0.5Lux/F1.2	0.8Lux/F1.2	0.8Lux/F1.2	0.008Lux/F1.2
Back Light Compensation	背光补偿	ON/OFF Switchable			
Gain Control	增益控制	ON/OFF Switchable			
Video Output	视频输出	1.0Vp-p 75Ω BNC			
Power Requirement	所需电源	DC12V / AC24V Dual Voltage ± 10%			
Power Consumption	功率消耗	120 mA	150 mA	150 mA	170 mA
Operating Temperature	工作温度	-10°C ~ +50°C (14°F ~ 122°F)			

DIMENSIONS 尺寸示意图

