



WA系列一体化摄像机 WA Series All-In-One Camera



Features

- Sony Hi-Res. Super HAD CCD Sensor
- 420TV Lines or 480TV Lines of Horizontal Resolution
- AES, AGC, AWB
- High Sensitivity
- Minimum illumination of 0.5 Lux
- Built-in Vari-focal Lens
- Weatherproof
- CDS Automatic IR Trigger ON/OFF
- Low Smear
- Strong Back Light Compensation
- DC12V Input
- Low Power Consumption

SPECIFICATIONS 规格

Model No.	型号	WA-242PS	WA-248PS	WA-242PSI	WA-248PSI
Image Sensor	图像传感器	Sony Super HAD CCD			
Signal System	信号系统	PAL / NTSC			
CCD Size	CCD 尺寸	1/3"	1/3"	1/3"	1/3"
Effective Pixels	有效像素	PAL: 752(H)x582(V)		NTSC: 768(H)x494(V)	
Horizontal Resolution	水平清晰度	420TV Lines	480TV Lines	420TV Lines	480TV Lines
Sync. System	同步方式	Internal			
Electronic Shutter	电子快门	Auto: PAL: 1/50~1/100,000(sec.) NTSC: 1/60~1/110,000(sec.)			
Auto Iris Lens	自动光圈镜头	DC / Manual			
Gamma Characteristic	γ 特性	0.45			
White Balance	白平衡	AUTO			
S/N Ratio	信噪比	More than 48dB(AGC OFF)			
Lens Mount	可配镜头	3.5 - 8mm Vari-focal Lens			
Minimum Illumination	最低照度	0.5 Lux/F1.2	0.8 Lux/F1.2	0 Lux/F1.2	0 Lux/F1.2
Infrared Lamps	红外灯	Built-in 12pcs Infrared Lamps			
Infrared Visible Distance	红外照射距离	15 M			
Back Light Compensation	背光补偿	AUTO			
Gain Control	增益控制	AUTO			
Video Output	视频输出	1.0V p-p 75Ω BNC			
Power Requirement	所需电源	DC12V ± 10%			
Power Consumption	功率消耗	120 mA	150 mA	200 mA	230 mA
Operating Temperature	工作温度	-10°C ~ +50°C (14°F ~ 122°F)			

DIMENSIONS 尺寸示意图

