

FOSHAN RUNYANG LIGHTING CO.,LTD.

Add:Jiebian Industrial Zone,Luocun,Nanhai,Foshan,Guangdong,China

Tel:+86-757-8619 5111

Fax:0757-8644 3933

web:http://www.runyanglighting.com

Energy efficiency rating standard

W(w)	B	C	D	E	F	G	Class Rating
5	9.49	6.00	4.53	3.54	2.67	2.62	Min lumens (lm/w)
8	12.13	7.87	6.03	4.78	3.66	3.58	
10	13.43	8.82	6.81	5.43	4.18	4.10	
15	15.52	10.60	8.28	6.69	5.21	5.11	
20	17.48	11.86	9.35	7.61	5.98	5.86	
25	18.73	12.83	10.18	8.32	6.59	6.46	
35	20.53	14.25	11.40	9.39	7.50	7.35	
40	21.21	14.79	11.87	9.80	7.86	7.70	
50	22.30	15.66	12.63	10.48	8.44	8.27	
60	23.14	16.35	13.22	10.01	8.90	8.73	
75	24.12	17.14	13.92	11.63	9.45	9.26	
	Our high light efficiency JC bulbs	Our normal light efficiency JC bulbs					
		Our high light efficiency JD bulbs in future	Our normal light efficiency JD bulbs				

Technical Parameter of our JC bulbs

Specification	Power(W)	Normal light efficiency (Energy Class C)			High light efficiency (Energy Class B)		
		Color temperature (K) ≥	Luminous Flux (lm) ≥	Lumens (lm/w) ≥	Color Temperature (K) ≥	Luminous Flux (lm) ≥	Lumens (lm/w) ≥
JC SERIES							
6V5W	5	2750	35	7	3000	50	10
6V8W	8	2750	64	8	3000	100	12.5
6V10W	10	2800	90	9	3050	140	14
6V20W	20	2800	240	12	3050	370	18.5
6V35W	35	2850	525	15	3100	752.5	21.5
6V50W	50	2850	800	16	3100	1175	23.5
12V5W	5	2800	35	7	3050	50	10
6V8W	8	2800	64	8	3050	100	12.5
12V10W	10	2850	90	9	3100	140	14
12V20W	20	2850	240	12	3100	370	18.5
12V25W	25	2850	350	14	3100	500	20
12V35W	35	2900	525	15	3150	752.5	21.5
12V50W	50	2900	800	16	3150	1175	23.5
12V75W	75	2900	1350	18	3200	1875	25
12V100W	100	2900	1850	18.5	3200	2550	25.5
24V5W	5	2700	35	7	2950	50	10
24V10W	10	2750	90	9	3000	140	14
24V20W	20	2750	240	12	3000	370	18.5
24V35W	35	2800	525	15	3050	752.5	21.5
24V50W	50	2800	800	16	3050	1175	23.5
24V75W	75	2800	1350	18	3050	1875	25
24V100W	100	2800	1850	18.5	3050	2550	25.5

Technical Parameter of our JD bulbs

Specification	Power(W)	Normal light efficiency (Energy Class D)			High light efficiency (Energy Class C)		
		Color temperature (K) ≥	Luminous Flux (lm) ≥	Lumens (lm/w) ≥	Color Temperature (K) ≥	Luminous Flux (lm) ≥	Lumens (lm/w) ≥
JD Series							
120V20W	20	2550	190	9.5	2650	240	12
120V25W	25	2600	262.5	10.5	2700	325	13
120V35W	35	2700	402.5	11.5	2800	507.5	14.5
120V40W	40	2750	480	12	2850	620	15.5

120V50W	50	2800	650	13	2900	800	16
120V60W	60	2850	810	13.5	2950	1020	17
120V75W	75	2900	1050	14	3000	1312.5	17.5
230V20W	20	2550	190	9.5	2650	240	12
230V25W	25	2600	262.5	10.5	2700	325	13
230V35W	35	2700	402.5	11.5	2800	507.5	14.5
230V40W	40	2750	480	12	2850	620	15.5
230V50W	50	2800	650	13	2900	800	16
230V60W	60	2850	810	13.5	2950	1020	17
230V75W	75	2900	1050	14	3000	1312.5	17.5
240V20W	20	2550	190	9.5	2650	240	12
240V25W	25	2600	262.5	10.5	2700	325	13
240V35W	35	2700	402.5	11.5	2800	507.5	14.5
240V40W	40	2750	480	12	2850	620	15.5
240V50W	50	2800	650	13	2900	800	16
240V60W	60	2850	810	13.5	2950	1020	17
240V75W	75	2900	1050	14	3000	1312.5	17.5