



\*\*\*PROOF OF QUALITY

ADD: NO.351 SHAOXING ROAD, HANGZHOU, CHINA  
TEL:0086-571-85386671,85386672,85386673  
FAX:0086-571-85386676  
[Http://www.hzdongdi.com](http://www.hzdongdi.com) [www.ddsafety.cn](http://www.ddsafety.cn)  
E-MAIL:[sale@ddsafety.cn](mailto:sale@ddsafety.cn) [info@ddsafety.cn](mailto:info@ddsafety.cn)

---

HANGZHOU DONGDI IMP. & EXP. CO., LTD

1

## EN Standards information(From Hangzhou DongDi)

### EN 420 General Requirements

#### Markings

Each glove carries the DONGDI logo, the reference, the size and CE mark. If it is classed in category III, the number of the notified body that carried out the tests also appears on the glove.

#### Dexterity (1-5)

The vast majority of DONGDI gloves offer maximum dexterity (5).

#### Innocuousness (pH)

All DONGDI gloves are checked for compliance in terms of their pH value (between 3.5 and 9.5).

#### Performance levels

The higher the rating, the greater the performance, the lowest rating being zero.



ADD: NO.351 SHAOXING ROAD, HANGZHOU, CHINA

TEL:0086-571-85386671,85386672,85386673

FAX:0086-571-85386676

[Http://www.hzdongdi.com](http://www.hzdongdi.com) [www.ddsafety.cn](http://www.ddsafety.cn)

E-MAIL:[sale@ddsafety.cn](mailto:sale@ddsafety.cn) [info@ddsafety.cn](mailto:info@ddsafety.cn)

\*\*\*PROOF OF QUALITY

HANGZHOU DONGDI IMP. & EXP. CO., LTD

## EN 388 Mechanical Risks .

The glove's resistance to abrasion, cutting, tearing puncturing is laboratory tested. The figures shown for each glove, beneath the symbol for this standard, should be interpreted as follows:

### PERFORMANCE LEVELS

(a): 0 to 4

(b): 0 to 5

(c): 0 to 4

(d): 0 to 4



### REQUIREMENTS:

RESISTANCE TO ABRASION (A)

Number of cycles required for the sample to fail, at a constant speed.

RESISTANCE TO CUTTING BY SLICING (B)

Index calculated from the number of cycles required to cut the sample at a constant speed.

RESISTANCE TO TEARING (C)

Force required to tear the sample.

RESISTANCE TO PUNCTURING (D)

Force required to pierce the sample with a standard steel punch.

## EN 374-3 Chemical Risks

The time taken to penetrate the glove (permeation) is measured in a laboratory. To find out the chemical resistance of the materials used, check the table Comparison Chart on the site.

### PERFORMANCE LEVELS

0 to 6

### REQUIREMENTS:

PERMEATION





ADD: NO.351 SHAOXING ROAD, HANGZHOU, CHINA

TEL:0086-571-85386671,85386672,85386673

FAX:0086-571-85386676

[Http://www.hzdongdi.com](http://www.hzdongdi.com) [www.ddsafety.cn](http://www.ddsafety.cn)

E-MAIL:[sale@ddsafety.cn](mailto:sale@ddsafety.cn) [info@ddsafety.cn](mailto:info@ddsafety.cn)

\*\*\*PROOF OF QUALITY

HANGZHOU DONGDI IMP. & EXP. CO., LTD

## EN 511 Cold-related Risks

The tests determine the glove's level of performance in cold climates or artificially cold environments where the cold is transferred by convection and/or through contact. It may also be mentioned whether the glove is waterproof.



### PERFORMANCE LEVELS

(a): 0 to 4

(b): 0 to 4

(c): 0 to 1

REQUIREMENTS:

RESISTANCE TO CONVECTIVE COLD (A)

RESISTANCE TO CONTACT COLD (B)

IMPERMEABILITY TO WATER (C)

## EN 374-2 Micro-organisms Risks



The glove is deemed to be resistant to micro-organisms if it has successfully undergone the penetration test this standard requires.

REQUIREMENTS:

PENETRATION - air or water leakage test



## 2002/72 EC Food Compatibility

European directive 2002/72 (which replaces 90/128/EEC) governs the conditions and restrictions that all plastic materials and objects must comply with if they are intended to come into contact with foods.

## EN1149-1 Antistatic properties

The glove attains the levels of resistivity required by this standard in terms of electrostatic conduction or dissipation.