



## 东营明德石油科技有限公司

Dongying Mingde Petroleum Technology Co., Ltd.

Add.: No 739, Beiyi Road, Dongying District, Dongying, Shandong, China 257061

T: 86-546-8395661, F: 86-546-8521870 M: +86 13589953895 E: [slottedcreensales@163.com](mailto:slottedcreensales@163.com)

[www.mindeoil.com](http://www.mindeoil.com)

### Slotted Liner

Slotted liners have been used for many years to provide sand control in many oil industry applications. They are commonly applied in reservoirs that produce high-viscosity oil from horizontal wells with unconsolidated, high-permeability sands.

#### Specification

1	Outside Diameter (mm)	$\Phi 50 \sim \Phi 219$ (API 5CT 2-3/8"-8-5/8")
2	Length of the liner (mm)	1000~12000
3	Slot width (mm)	0.15~0.60(Tolerance $\pm 0.03$ ), 0.60~4.00(Tolerance $\pm 0.1$ )
4	Slot length (mm)	As per customers' request, Tolerance $\pm 1.00$
5	Slot quantities per circle	As per customers' request
6	The distance between the adjacent slots (mm)	As per customers' request



Slotted liner has been extensively applied in Xinjiang Oilfield, Shengli Oilfield, Zhongyuan Oilfield, Yanchang Oilfield, India and Kazakhstan with its unique superiority and proven customer approval. It can be used for Huff & Puff, SAGD oil production in heavy oil and super heavy oil oilfield. The annual production is over 80,000 meters. We can provide straight slotted liner and keystone slotted liner as per clients' requirement.