



GREEN LIGHTING


Green Lighting Electronics Co.,Ltd


NO2 ,5Xiang, Da Pu Xin Cun Industrial , LongDong Community, LongGang District,ShenZhen,China


Tel: +86-755-84829400 Fax: +86-755-84820206

Website: www.szglighting.com

Cord Mining Cap Lamp

Model	Picture	Technical Specs	
GL12LM-A		Light source	1pcs main light and 2pcs auxiliary lights
		Battery capacity	10.4Ah
		Rated Voltage	3.7V
		Main light current (strong light)	800mA
		Main light current (working light)	450mA
		Power of the main light (strong light)	2.4W
		Power of the main light (working light)	1.4W
		Illuminous(strong light)	334LUM
		Illuminous(working light)	195LUM
		Brightness of the main light (strong light)	25000lux
		Brightness of the main light (working light)	15000lux
		Life span for main LED	100000hours
		Battery cycles	1200 cycles
		Working time (Strong Light)	13 hours
		Working time (working light)	22 hours
		4 Levels light	working light- strong light- auxiliary lights-SOS
		Weight	650g
		Water-proof grade	IP68
		Certified	CE&ATEX

GL5LM-A		Light source	1pcs main light and 6 auxiliary lights
		Battery capacity	6.6Ah
		Rated Voltage	3.7V
		Main light current	300mA
		Power of the main light	0.9W
		Illuminous	125LUM
		Brightness of the main light	4000lux
		Life span for main LED	100000hours
		Battery cycles	1200 cycles
		Working time	22 hours
		Cable length	1.4m Or 1.6m
		Weight	472g
		Water-proof grade	IP67
		Certified	CE&ATEX

GL5LM-B		Light source	1pcs main light and 6pcs auxiliary lights
		Battery capacity	6.6Ah
		Rated Voltage	3.7V
		Main light current	350mA
		Power of the main light	1.05W
		Illuminous	146LUM
		Brightness of the main light	10000lux
		Life span for main LED	100000hours
		Battery cycles	1200 cycles
		Working time	18 hours
		Cable length	1.4m Or 1.6m
		Weight	478g
		Water-proof grade	IP67
		Certified	CE&ATEX

GL5LM-C





Light source	1pcs main light and 2pcs auxiliary lights
Battery capacity	6.6Ah
Rated Voltage	3.7V
Main light current	350mA
Power of the main light	1.05W
Illuminous	146LUM
Brightness of the main light	12000lux
Life span for main LED	100000hours
Battery cycles	1200 cycles
Working time	18 hours
Cable length	1.4m Or 1.6m
Weight	490g
Water-proof grade	IP67
Certified	CE&ATEX


GLT-7A





Light source	1pcs main light and 6pcs auxiliary lights
Battery capacity	6.6Ah
Rated Voltage	3.7V
Main light current	300mA
Power of the main light	0.9W
Illuminous	125LUM
Brightness of the main light	12000lux
Life span for main LED	100000hours
Battery cycles	1200 cycles
Working time	22 hours
Cable length	1.4m Or 1.6m
Weight	560g
Water-proof grade	IP67
Certified	CE&ATEX

GLT-7B		Light source	1pcs main light and 6pcs auxiliary lights
		Battery capacity	6.6Ah
		Rated Voltage	3.7V
		Main light current	350mA
		Power of the main light	1.05W
		Illuminous	146LUM
		Brightness of the main light	10000lux
		Life span for main LED	100000hours
		Battery cycles	1200 cycles
		Working time	18 hours
		Cable length	1.4m Or 1.6m
		Weight	560g
		Water-proof grade	IP67
		Certified	CE&ATEX

GLT-7C		Light source	1pcs main light and 2pcs auxiliary lights
		Battery capacity	6.6Ah
		Rated Voltage	3.7V
		Main light current	400mA
		Power of the main light	1.2W
		Illuminous	167LUM
		Brightness of the main light	15000lux
		Life span for main LED	100000hours
		Battery cycles	1200 cycles
		Working time	16 hours
		Cable length	1.4m Or 1.6m
		Weight	569g
		Water-proof grade	IP67
		Certified	CE&ATEX

GL6-A		Light source	1pcs main light and 4pcs auxiliary lights
		Battery capacity	11.2Ah
		Rated Voltage	3.7V
		Main light current	600mA
		Power of the main light	1.8W
		Illuminous	250LUM
		Brightness of the main light	50000lux
		Life span for main LED	100000hours
		Battery cycles	1200 cycles
		Working time	18 hours
		Cable length	1.4m Or 1.6m
		Weight	722g
		Water-proof grade	IP67
		Certified	CE&ATEX

GL6-B		Light source	1pcs main light and 4pcs auxiliary lights
		Battery capacity	11.2Ah
		Rated Voltage	3.7V
		Main light current	700mA
		Power of the main light	2.1W
		Illuminous	295LUM
		Brightness of the main light	30000lux
		Life span for main LED	100000hours
		Battery cycles	1200 cycles
		Working time	16 hours
		Cable length	1.4m Or 1.6m
		Weight	722g
		Water-proof grade	IP67
		Certified	CE&ATEX


GL8LM		Light source	1pcs main light and 2pcs auxiliary lights
		Battery capacity	7.8Ah
		Rated Voltage	3.7V
		Main light current	550mA
		Power of the main light	1.65W
		Illuminous	230LUM
		Brightness of the main light	15000lux
		Life span for main LED	100000hours
		Battery cycles	1200 cycles
		Working time	15 hours
		Cable length	1.4m Or 1.6m
		Weight	550g
		Water-proof grade	IP67
		Certified	CE&ATEX


Cordless Cap Lamp


Hot sell !!! New cordless cap lamp with OLED display.


13000lux high brightness, OLED screen display the time, battery capacity and client's company information.

Beautiful appearance, 210g light weight is more portable. **Magnetic USB charger**

GLC-6A		Light source	1pcs main light and 2pcs auxiliary lights
		Battery capacity	6.2Ah
		Rated Voltage	3.7V
		Main light current	300mA
		Power of the main light	0.9W
		Illuminous	125LUM
		Brightness of the main light	13000lux
		Life span for main LED	100000hours
		Battery cycles	1200 cycles
		Working time	20 hours
		3 Levels Light	Strong light- auxiliary lights- SOS
		Weight	210g
		Water-proof grade	IP68
		Certified	CE&ATEX

GL2.5LM-A		Light source	1pcs main light and 6pcs auxiliary lights
		Battery capacity	2.8Ah
		Rated Voltage	3.7V
		Main light current	230mA
		Power of the main light	0.69W
		Illuminous	96LUM
		Brightness of the main light	3500lux
		Life span for main LED	100000hours
		Battery cycles	1200 cycles
		Working time	13 hours
		Weight	128g
		Water-proof grade	IP67
		Certified	CE&ATEX

GL2.5LM-B		Light source	1pcs main light
		Battery capacity	2.8Ah
		Rated Voltage	3.7V
		Main light current	500mA
		Power of the main light	1.5W
		Illuminous	210LUM
		Brightness of the main light	10000lux
		Life span for main LED	100000hours
		Battery cycles	1200 cycles
		Working time	6 hours
		Weight	152g
		Water-proof grade	IP67
		Certified	CE&ATEX

GL4.5LM		Light source	1pcs main light and 6pcs auxiliary lights
		Battery capacity	4.5Ah
		Rated Voltage	3.7V
		Main light current	300mA
		Power of the main light	0.9W
		Illuminous	125LUM
		Brightness of the main light	4000lux
		Life span for main LED	100000hours
		Battery cycles	1200 cycles
		Working time	15 hours
		Weight	234g
		Water-proof grade	IP67
		Certified	CE&ATEX

GL2-A




Light source	1pcs main light and 6pcs auxiliary lights
Battery capacity	2.2Ah
Rated Voltage	3.7V
Main light current	200mA
Power of the main light	0.6W
Illuminous	85LUM
Brightness of the main light	4000lux
Life span for main LED	100000hours
Battery cycles	1200 cycles
Working time	11 hours
Weight	171g
Water-proof grade	IP67
Certified	CE&ATEX

GLT-2



Light source	1pcs main light and 6pcs auxiliary lights
Battery capacity	2.2Ah
Rated Voltage	3.7V
Main light current	200mA
Power of the main light	0.6W
Illuminous	85LUM
Brightness of the main light	4000lux
Life span for main LED	100000hours
Battery cycles	1200 cycles
Working time	11 hours
Weight	171g
Water-proof grade	IP67
Certified	CE&ATEX

GL5		Light source	1pcs main light and 2pcs auxiliary lights
		Battery capacity	6.6Ah
		Rated Voltage	3.7V
		Main light current	450mA
		Power of the main light	1.4W
		Illuminous	200LUM
		Brightness of the main light	11000lux
		Life span for main LED	100000hours
		Battery cycles	1200 cycles
		Working time	15 hours
		Weight	250g
		Water-proof grade	IP67
		Certified	CE&ATEX

Tel: +86-755-84829400 Fax: +86-755-84820206

Website: www.szglighting.com