

Power	1300W	2600W	600W	1000W	3000W	4000W	5000W	7500W
Paraneters								
Item	B4B060-1300W-2	B4B060-2600W-2	B4B060-600W	B4B060-1000W	B4B060-3000W	B4B060-4000W	B4B060-5000W	B4B060-7500W
Picture	 2-color lights Or 1 color 							
Voltage	AC220-240V	AC220-240V	AC220-240V	AC220-240V	AC220-240V	AC220-240V	AC220-240V	AC220-240V
LED Qty	1334pcs	2668pcs	960pcs	1920pcs	3024pcs	4032pcs		
Color	W/R/G/W+G/ W+R/R+G	W/R/G/W+G/ W+R/R+G	White/Green /Red/Blue	White/Green /Red/Blue	White/Green /Red/Blue	White/Green /Red/Blue	White/Green /Red/Blue	White/Green /Red/Blue
Cable Length	15M	15M	15M	15M	15M	15M cable	15M cable	15M cable
Lamp Size (mm)	156x340	156x500	156x340	156x500	156x780	156x780	156x780	156x1050
Packing Size (cm)	33x33x53	33x34x70	33x33x53	33x34x70	29x29x74.5	35*35*70	35*35*70	35*35*95
Weight (kg)	9	13	13	19	20	22	22	26
Beam Angle	360°	360°	360°	360°	360°	360°	360°	360°
Material	SUS+AL+PMMA	SUS+AL+PMMA	SUS+AL+PMMA	SUS+AL+PMMA	SUS+AL+PMMA	SUS+AL+PMMA	SUS+AL+PMMA	SUS+AL+PMMA
Working Temperture	≤30℃	≤30℃	≤30℃	≤30℃	≤30℃	≤30℃	≤30℃	≤30℃

Comlite LED Limited

WhatsApp: 0086 159 8665 8054

Web: www.comlite-led.com

www.comlitestore.com

Email: sales@comlite-led.com

sales@comlitestore.com

Skype / WeChat: comlite

200-245V 15meter cable Underwater fishing lights

Power Parameters	140W	200W	300W	400W Hot!	500W	150W	250W	450W NEW	600W
Item	B4B060-140W	B4B060-200W	B4B060-300W	B4B060-400W	B4B060-500-2	B4B060-N150W	B4B060-N250W	B4B060-N450W	B4B060-N600W
Picture									
Voltage	DC12	DC12	DC12	DC12	DC12V	DC12-24V	DC12V - 24V	DC12V -24V	DC12-24V
LED Qty	420 PCS	588 PCS	840 PCS	864 PCS	864 PCS	324 PCS	432 PCS	864 PCS	640 PCS
Lumen	White: 9600lm Green: 7800lm	White: 13200lm Green: 11000lm	White: 25000lm Green: 23000lm	White: 44000lm Green: 40000lm	G+W W+R G+R B+W...	White: 15000lm Green: 13000lm	White: 23800lm Green: 20000lm	White: 44000lm Green: 40000lm	White: 80000lm Green: 60000lm
Cable Length	5M	5M	5M	5M	5M	5M	5M	5M	5M
Lamp Size (mm)	80*368	80*388	80*468	80*468	80*468	80*260 mm	80*310	80*460	100*460 mm
Packing Size (cm)	38*15*9	44*10*19	51*19*9	51*19*9	51*19*9 cm	38*15*9	38*15*9	51*19*9	51*19*9 cm
Weight (kg)	1.9	2.5	2.95	3.3	3.5	1.3	2.2	3.2	3.5
Beam Angle	360°	360°	360°	360°	360°	360°	360°	360°	360°
Material	AL+PC	AL+PC	AL+PC	AL+PC	AL+PC	AL+PC	AL+PC	AL+PC	AL+PC+SUS
Case	-	-	-	-	-	/	Yes	Yes	/
Working Temperture	≤30°C	≤30°C	≤30°C	≤30°C	≤30°C	≤30°C	≤30°C	≤30°C	≤30°C

Comlite LED Limited

WhatsApp: 0086 159 8665 8054

Web: www.comlite-led.com

www.comlitestore.com

Email: sales@comlite-led.com

sales@comlitestore.com

Skype / WeChat: comlite

Medium power high brightness 5meter cable Underwater lights
Color: White/Blue/Green/Red/Orange/Warmwhite/Golden

Comlite

Power Parameters	8W	20W	60W	30W	60W	60W
Item	B4B060-8W	B4B060-20W	B4B060-60W	B4B060-30W	B4B060-60W	B4B060-60W-12V
Picture						
Voltage	DC12-24V	AC/DC12-24V	DC12V	DC12-24V	DC12-24V	DC12V
LED Qty	180pcs	4pcs COB	4pcs COB	70pcs	126pcs	135pcs
Lumen	White: 800lm Green: 600lm Blue: 160lm	White: 1350lm Green: 1000lm	White: 5400lm Green: 5400lm Blue: 3600lm	White: 3300lm Green: 2400lm	White: 5400lm Green: 5200lm	White: 5400lm Green: 5200lm
Cable Length	6M	5M	5M	6M	6M	6M
Lamp Size (mm)	30*180	41*195	335*40	38*50	80*120	80*120
Packing Size (cm)	24*13*5	24*13*5	54*9*5	24x13x5	18x15x17	18x15x17
Weight (kg)	0.6	0.8	0.9	0.7	1.4	1
Beam Angle	360°	360°	360°	360°+120°	360°+120°	360°+120°
Material	AL+PC	AL+PC	AL+PC	AL+PC	AL+PC	AL+PC
Working Temperature (In Water)	≤30°C	≤30°C	≤30°C	≤30°C	≤30°C	≤30°C

Comlite LED Limited

Abbie Tian

WhatsApp: 0086 159 8665 8054

Web: www.comlite-led.com

www.comlitestore.com

Email: sales@comlite-led.com

sales@comlitestore.com

Skype / WeChat: comlite

Small Underwater fishing lights

Power Parameters	400W	800W	1200W	1600W	600W	600W	1200W	1200W
Item	B4B060-A400W	B4B060-A800W	B4B060-A1200W	B4B060-A1600W	B4B060-E600W	B4B060-E600W2	B4B060-E1200W	B4B060-E1200W2
Picture								
Lamp Size(mm)	425*402*278	833x402x278	1241*402*278	825*812*278	D490x330	D490x330	D645x380	D645x380
LED Qty	448pcs SMD3030	896pcs SMD3030	1344pcs SMD3030	1792pcs SMD3030	240pcs SMD5050	240pcs SMD5050	480pcs SMD5050	480pcs SMD5050
Lumen	White/Golden 44000LM	White/Golden 88000LM	White/Golden 132000LM	White/Golden 176000LM	White/Golden 66000LM	White/Golden 66000LM	White/Golden 132000LM	White/Golden 132000LM
Packing Size (mm)	530*490*225	530*900*225	530*1310*225	940*910*225	620*495*230	620*520*250	855*675*260	855*675*260
Weight (kg)	16.5	29	38	52	20.5	21	35	36
Voltage	100-265VAC	100-265VAC	100-265VAC	100-265VAC	100-265VAC	100-265VAC	100-265VAC	100-265VAC
Beam Angle	10°, 60°, 120°				10°, 25°, 45°, 60°			
Cable Length	30CM	30CM	30CM	30CM	30CM	30CM	30CM	30CM
IP Rate	IP65	IP65	IP65	IP65	IP65	IP65	IP65	IP65
Material	AL+PC	AL+PC	AL+PC	AL+PC	AL+PC	AL+PC	AL+PC	AL+PC
Shape color	Black / Silver	Black / Silver	Black / Silver	Black / Silver	Black / Silver	Black / Silver	Black / Silver	Black / Silver

If you want MeanWell Driver, please contact us for the price.

Comlite LED Limited

Abbie Tian

WhatsApp: 0086 159 8665 8054

Web: www.comlite-led.com

www.comlitestore.com

Email: sales@comlite-led.com

sales@comlitestore.com

Skype / WeChat: comlite

100-240VAC On board LED lights, IP65