



Shenzhen Netoptouch Technology Co.,Ltd

Add: Floor 4, Block 5, Lehuahang, No.37, Kengwei Blvd, Shangwu, Shiyao, Bao'an, Shenzhen, China

Email: sales01@netoptouch.com Web: <http://en.netoptouch.com>


Tel: +86-755-83277181 Whatsapp/Wechat/Cellphone: +86-13544143658

15" All in one touch panel PC

Pic for reference final will be shown (Customised Solution)



OS	Windows 7/8/10 or Linux available
Motherboard	Industrial motherboard
CPU	Intel I3 4005U generation processor
RAM	8GB DDRIII
Storage	128GB SSD
Interface of motherboard	1*LAN, 2*Com, 8*USB, 1*MSATA, 2*SATA 3.0, 1*NB DDR3




Panel Parameter, 15"

Panel size	Auo A150XN01 TFT LCD
Active Area	304.128 (H) x 228.096
Pixel Pitch	0.297(per one triad)x0.297
Pixel Arrangement	R.G.B. Vertical Stripe
Cell Transmittance	[%] (8.8)
Optical ResponseTime	[msec] 12 (Typ, on/off)
Aspect Ratio	4 : 3
Resolution	1024x768
Color	8bits, 16.7m true color
Physical Size(HxVxD)	316.23(W)x242.55(H)x1.9(D)(Typ)
Contrast	500:1
Visual Angle(H/V)	80/80/80/80°



Touch Screen Parameter (G+G structure)

Touch technology	Capacitive touch panel, Maximum 10 points touch
Position accuracy	±1mm relative, No drift

Alignment	Software drivers provide a calibration facility
Speed of response&Resolution&Life long	8ms, 4096x4096, 60 000 000 cycle times
Others	Transmittance: more than 90%
	Thickness of glass: 6H
	Interface: USB, no need driver
	
Other Items	
Whole body material	Aluminium+steel, size: 361.65x285.65mm
Speaker	2*10W speakers inside
Heat Dispersion	Built-in DC fans
Wifi	Excluding
4G router	Quectel EC 25 4G router
Power input	AC 220V~240V, 50/60 HZ
Power in standby	≤30W
Power in working	30W-100W
Default Surface Painting	Powder painting, multi color for choice

