

Shenzhen Netoptouch Technology Co., Ltd.

Address: 4th Floor, Block 5, Lehuahang, No. 37, Kengwei Blvd, Shangwu, Shiyan, Baoan, Shenzhen, China

Skype: netoptouch Email: sales01@netoptouch.com; Website: http://en.netoptouch.com

TEL: 0086-755-83277181

Spec of 55" floor Standing double sided digital kiosk



Panel	Screen size	55 inch, 2pcs
	Active size	1209.6(H)*680.4(V)mm
	Pixel pitch	105(H) ×3(RGB)×315(V)μm
	Pixel arrangement	Pixels RGB Z-stripe
	Display colors	1.07G (8bits + FRC)
	Display mode	Transmission mode, Normally Black
	Open Cell Transmittance	5.0%(TYP)(At center point with BOE BLU)
	Weight	2370(TYP) gram
	Power Consumption	12(TYP) Watt, with TCON board
	Max resolution	1920x1080
	Surface Treatment	Front Polarizer: Haze 1%, 3H, Anti glare treatment Bottom Polarizer: Clear
	Viewing Angle	89/89/89/89
	Contrast Ratio	1000:1(Min), 1200:1(Typical)
	Brightness	300cd/m2
	Aspect Ratio	16:9
Response time	8ms(Typical), 10ms(Max)	
Embedded PC	CPU	RK3288 Cortex-A17 quad-core, up to 1.8GHz
	Storage	8GB
	Memory	2GB
	WiFi	Built-in high performance SDIO interface Wi-Fi module, support IEEE 802.11 b/g/n
	Ethernet	10/100M Adaptive Ethernet RJ45 connector+4-Pin header
	Interface	2 horizontal connectors (Single Socket), 1 OTG pin header, 1 Micro-USB, 4 TTL/RS-232 serial port.
	Others	5-way GPIO signals for such as GPIO buttons and/or 3.3V digital input/output 8 Ohm 6W Dual Audio Amplifier Output
Power	Power input	AC100-240V(power adaptor)
General information	Case Material	Metal case, temper/AG glass at front side
	Case Color	Standard color: Black&Silver(Customized color upon request)
	Storage Temp	(-20 -- 60degree)
	Working Temp	(0 -- 60degree)
	Storage/Working Humidity	(10 -- 90%)
	Certificates	CE, FCC&Rohs
	Support format of content	Supported audio, video, photo formats: RMVB, FLV, MPEG1/2/4, AVI, WMV9, MOV, MP4, TS M2T, VOB, MP3, WMA, WAV, EAAC+, MP2 Dec, AC3, FLAC, APE, BSAC, etc., BMP, PNG, GIF, JPEG, etc.
Please note	All pictures above are only for reference, please make the object as the standard.	