

Shenzhen Netoptouch Technology Co., Ltd.

Address: 4rd Floor, Block 5, Lehuahang, No. 37, Kengwei Blvd, Shangwu, Shiyuan, Baoan, Shenzhen


Skype: netoptouch Email: sales01@netoptouch.com; Website: www.netoptouch.cc

TEL: 0086-755-8327181

Spec of 55" floor Standing digital kiosk



Panel	Screen size	55 inch
	Max resolution	4096x2160
	Viewing Angle	178
	Colour Brightness	16.7M
	Contrast Ratio	1000:1
	Brightness	500cd/m2
	Aspect Ratio	16:9
	Interface	VGA/DVI/HDMI
	Response time	6.5ms
	Glass	Anti-reflection glass
Embedded PC (Android 7.1)	CPU	RK3288 chip
	Storage	16GB
	Memory	4GB
	TF Card	Self-elastic Micro SD card socket, up to 32GB capacity
	LVDS	30 Pin industrial standard dual LVDS interface, support
	WiFi	High-performance WIFI 802.11b/g/n
	Interface	USB*8/OTG/TTL pin headers/TTL&RS 232 pin connector DC12V/HDMI/LAN/SD
Audio	Built-in stereo speakers	5W*2
Power	Power input	AC100-240V(power adaptor)
General Information	Case Material	Metal case, temper/AG glass at front side
	Case Color	Standard color: Black&Silver(Customized color upon
	Storage Temp	(-20 -- 60degree)
	Working Temp	(0 -- 40degree)
	Storage/Working Humidity	(10 -- 90%)
	Certificates	CE, FCC&Rohs

General information	Functions of software	Supports web / Flash, SD Card, horizontal and vertical scrolling, title scrolling, screen sharing, images, subtitle receiving media content via the network and remote block, run ads, broadcast regularly, streaming.
	Support format of content	Supported audio, video, photo formats: RMVB, FLV, MOV, MP4, TS M2T, VOB, MP3, WMA, WAV, AAC+, BSAC, etc., BMP, PNG, GIF, JPEG, etc.
Packing	Packing Weight	142kg
	Packing Size	198x35x99mm(2pcs)
	Packing: Cardboard box or Wooden case	 <p>Pictures are showed for your reference</p>
Please note	All pictures above are only for reference, please make the object as the standard	

hen, China
om



y
ting VESA/JEITA format

:tores,

request)

al screen mode, control of
titles, video, time, weather,
bers the place to be able to

MPEG1/2/4, AVI, WMV9,
MP2 Dec, AC3, FLAC, APE,



ence only.
ndard.