

Specification of 65"75" outdoor kiosk

One: Itemlist

Name	Components	Model Number
55" outdoor totem	Metal case	Made from 1.0mm~2.0mm SGCC Galvanized sheet steel, inner space with zinc-rich primer, surface covered with painting for outdoor use to protect the whole case, make the kiosk be able to be used at least 7 years.
	Anti-explosion glass	6mm toughened glass, compare to normal glass, toughened glass is with higher anti-vandal
	High brightness LED display	Special 2000cd/m2 brightness LED display for outdoor use, visible in the direct sunshine. Sensitometric to adjust brightness of display automatically to save power and lessen light pollution.
	Information play system	Support Android network information release system Support pictures, videos, text and so on Support wired/wireless/4G data transportation; Support U disk
	Electrical information	Leakage protection switch RTC function Grade C Surge protective device to avoid Instant lightning strike Meanwell industrial power supply to provide stable power.
	Cooling system	Cooling system via smart fan system, be able to work as normal when the temperature is -20℃~50℃;
	Test system	Spraying test Circulatory test during high low temperatures Test of solar radiation; Ageing test;

Two: Specification

Item	Components	Technical Data	
1	LED display, 2pcs for double -sided	Size	65inch/75 inch
		Active area	1428.4x803.4mm(65") 1650x928mm(75")
		Ratio	16 : 9
		Resolution	1920x1080/3840x2160
		Brightness	2000cd/m ²
		Response time	6ms
		Lifelong	More than 50 000 hours
		Color	16.7m
		View angle	178°Horizontal/178°Vertical
2	Android	Processor	RK3568
		Ram	2GB
		Storage	16GB
		Interface	USB*4 RJ45*1
3	Metal case	IP grade	IP55
		Mount type	Free standing
		Color	Black/White/Grey/Red
		Protective glass	6mm toughed glass
4	Update	Update of programmer	Online or Via USB
		Update of software	Online or Via control board
	Working Environment	Video output	VGA, HDMI output
		Audio	I/O input/output

5		Control of light	automatic light sensor
		Control of temperature	Via smart fans
		Working Temperature	-20°C to +45°C
		Working Humidity	5% to 95%
		Power supply	AC 220V
		Nosy	<65db
		Max Power consumption	<=1100w(65") <=1600w(75")
6	Others	Display mode	Horizontal, Vertical, Full screen, split
		Video format	MPG 1/2/4, AVI, MP4, TS, MK...
		Image format	GIF, JPEG, PNG, BNP
		Audio format	Mp3, 24 bit linear PCM 7.1
		Other format	PDF/RSS news/Weather Forecast
		RTC	Support

Three. Pictures



Drawings:



