

CULTIVATOR



MODEL	GT-8	GT-8D	GT-9	GT-9D
Engine	4.41kw diesel engine	4.85kw gasoline engine	6.3kw diesel engine	6.3kw diesel engine
Start model	Recoil start	Electric start	Recoil start	Electric start
Rated Output/Max. Speed	4.0kW/3600rpm	4.0kW/3600rpm	6.3kW/3600rpm	6.3kW/3600rpm
Max. Torque	12N.m	12N.m	17N.m	17N.m
Dry weight	116Kg	124Kg	140Kg	152Kg
Furrow Depth (circle tillage)	15~30 cm	15~30 cm	15~35 cm	15~35 cm
Furrow width (circle tillage)	75~105 cm	75~105 cm	75~135 cm	75~135 cm
Diameter of circle tine	φ 36 cm	φ 36 cm	φ 36 cm	φ 36 cm
Max. Rotate of speed (high gear)	114 r/min	114 r/min	114 r/min	114 r/min
Max. Rotate of speed (low gear)	65 r/min	65 r/min	65 r/min	65 r/min
Max. Rotate of Speed (reverse gear)	49 r/min	49 r/min	49 r/min	49 r/min
Max. Torque (Output axis)	220N.m	220N.m	280N.m	280N.m
Transmission mode	Gear transmission	Gear transmission	Gear transmission	Gear transmission
Work Efficiency	600~1200 sq.m/h	600~1200 sq.m/h	800~1600 sq.m/h	800~1600 sq.m/h
Standard equipment	One set Tiller rotor(l) use for dry-field, one set running wheel			