



Swaged External Thread Tension Rope.

外牙内牙拉索

- 316 grade stainless steel.
316级不锈钢

Rope Φ	a	b	f (mm)		
			Diameter Before swaged	Key width After swaging	Tol
3mm	M6	100	6.35	5.3	0-0.12
4 mm	M6	110	7.5	6.2	
4 mm	M8	117	7.5	6.2	
5 mm	M8	124	9	7.5	
5 mm	M10	130	9	7.5	
6 mm	M10	145	12.6	10.6	0-0.17
6 mm	M12	162	12.6	10.6	
8 mm	M12	180	16	13.6	0-0.2
8 mm	M16	200	16	13.6	
10 mm	M16	210	18	14.8	
10 mm	M20	230	18	14.8	

外牙拉索 Swaged External Thread Tension Rope.



Part No.		Rope Φ	a	b	L
Left Thread	Right Thread	mm	mm	mm	custom
201-0604	202-0604	4 mm	M6	110	custom
201-0804	202-0804	4 mm	M8	117	custom
201-0805	202-0805	5 mm	M8	124	custom
201-1005	202-1005	5 mm	M10	130	custom
201-1006	202-1006	6 mm	M10	145	custom
201-1206	202-1206	6 mm	M12	162	custom
201-1208	202-1208	8 mm	M12	180	custom
201-1407	202-1407	7 mm	M14	180	custom
201-1608	202-1608	8 mm	M16	200	custom
201-1610	202-1610	10 mm	M16	210	custom
201-2010	202-2010	10 mm	M20	230	custom

* Swaged capacity :4mm – 10mm



TALURIT equipment and technical support.
瑞典TALURIT设备和技术支持