



浙江天杰实业股份有限公司
ZHEJIANG TIANJIE INDUSTRIAL CORP.

Add: Linglong Economic Development Zone,
Lin'an Hangzhou, Zhejiang, China P.C.: 311301
Tel: +86-571-23656057 Fax: +86-571-23656098

Mobile: +86-13819127997
http://www.tianjecable.com
E-mail: will@tianjecable.com

QR 540JCAM109

75 Ohm Coaxial Cable
Trunk Cable



Physical specifications

Item	Material	Diameter
Inner conductor	CCA	3.15mm
Dielectric	Foamed Polyethylene	13.03mm
Outer Conductor	Welding Aluminum	13.72mm
Outer Conductor Thickness	Aluminum Tube	0.35 mm
Jacket	PE	15.49mm
Messenger	Steel	2.77 mm

Mechanical specifications

Minimum Bending Radius	16.5cm
Maximum Pulling Tension	100kgf
Breaking Strength of Messenger	816kgf

Electrical specifications

Capacitance	50±3pF/m
Impedance	75±3Ω
Nominal Velocity of propagation	87%

Resistance @ 68°F (20°C)

Inner conductor	3.34Ω/km
Out conductor	1.94Ω/km
Loop	5.28Ω/km

Attenuation @ 68°F (20°C)

5MHz	0.46dB/100m
55MHz	1.54dB/100m
83MHz	1.90dB/100m
211MHz	3.12dB/100m
250MHz	3.38dB/100m
300MHz	3.71dB/100m
350MHz	4.03dB/100m
400MHz	4.33dB/100m
500MHz	4.89dB/100m
550MHz	5.12dB/100m
600MHz	5.38dB/100m
750MHz	6.07dB/100m
865MHz	6.56dB/100m
1000MHz	7.12dB/100m

REACH



CE