

In-Wall Speaker Cable

Part No.	Description	Conductor	Insulation	Jacket
16/2-OFC-65S	16AWG 2C Speaker cable /Audio cable 65strand	65*0.16mm BC	2.1mm PVC	5.3mm PVC
16/2-OFC-26S	16AWG 2C Speaker cable /Audio cable 26strand	26*0.254mm BC	2.1mm PVC	5.3mm PVC
16/2-OFC-65S-HD	16AWG 2C Speaker cable /Audio cable 65strand Heavy Duty	65*0.16mm BC	2.1mm PVC	6.5mm PVC
16/4-OFC-65S	16AWG 4C Speaker cable /Audio cable 65strand	65*0.16mm BC	2.1mm PVC	6.5mm PVC
16/4-OFC-26S	16AWG 4C Speaker cable /Audio cable 26strand	26*0.254mm BC	2.1mm PVC	6.5mm PVC
16/4-OFC-65S-HD	16AWG 4C Speaker cable /Audio cable 65strand Heavy Duty	65*0.16mm BC	2.1mm PVC	7.2mm PVC
14/2-OFC-105S	14AWG 2C Speaker cable /Audio cable 105strand	105*0.16mm BC	2.65mm PVC	6.5mm PVC
14/2-OFC-105S-HD	14AWG 2C Speaker cable /Audio cable 105strand Heavy Duty	105*0.16mm BC	2.65mm PVC	7.3mm PVC
14/4-OFC-105S	14AWG 4C Speaker cable /Audio cable 105strand	105*0.16mm BC	2.65mm PVC	7.3mm PVC
14/4-OFC-105S-HD	14AWG 4C Speaker cable /Audio cable 105strand Heavy Duty	105*0.16mm BC	2.65mm PVC	8.0mm PVC
14/2-OFC-41S	14AWG 2C Speaker cable /Audio cable 42strand	41*0.254mm BC	2.65mm PVC	6.5mm PVC
14/4-OFC-41S	14AWG 4C Speaker cable /Audio cable 42strand	41*0.254mm BC	2.65mm PVC	7.3mm PVC
12/2-OFC-65S	12AWG 2C Speaker cable /Audio cable 65strand	65*0.254mm BC	3.3mm PVC	8.0mm PVC
12/4-OFC-65S	12AWG 2C Speaker cable /Audio cable 65strand	65*0.254mm BC	3.3mm PVC	9.4mm PVC

Note:

Insulation color: 2C Red Black // 4C Red Black White Green

Example of Cable Printing:

SPEAKER CABLE P/N.: 16/2-OFC-65S (UL) E230636 CL3R 2C 16AWG 65STRAND OXYGEN FREE COPPER (UL) E230635 CMR FT4 75C CE EU ROHS EC ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 ***FT

