



浙江天杰实业股份有限公司
ZHEJIANG TIANJIE INDUSTRIAL CORP.

Add: Linglong Economic Development Zone,
Lin'an Hangzhou, Zhejiang, China P.C.: 311301
Tel: +86-571-23656057 Fax: +86-571-23656098

Mobile: +86-13819127997
http://www.tianjecable.com
E-mail: will@tianjecable.com

UL Listed Sprinkler Wire/Irrigation Cable

Description:

UL 1493 Sprinkler Wire/Irrigation Cable

Applications:

Low energy landscape lighting, Sprinkler & Irrigation
Direct burial

Construction:

Conductors: Bare Copper
Insulation: PVC
Jacket: LDPE

Color Code of Insulation:

1.Red	6.Brown	11.Tan	16.Blue/White
2.White	7.Orange	12.Purple	17.Yellow/White
3.Green	8.Black	13.Natural	18.Brown/White
4.Blue	9.Pink	14.Red/White	19.Orange/White
5.Yellow	10.Gray	15.Green/White	

Electrical Properties:

Temperature Rating: -20°to 60°C
Operating Voltage: 30V

Construction Parameters:

Jacket Color: Black
Packaging: Usually in 1000' and 500' spools. Other length available

No. Conductor	Size (AWG)	Strand/Solid	Insulation dia.Nom.	Jacket wall Nom.	Jacket O.D. Nom.
2	18	Solid	1.85mm	0.66mm	4.42mm
3	18	Solid	1.85mm	0.66mm	4.67mm
4	18	Solid	1.85mm	0.66mm	5.08mm
5	18	Solid	1.85mm	0.66mm	5.51mm
6	18	Solid	1.85mm	0.66mm	5.97mm
7	18	Solid	1.85mm	0.66mm	5.97mm
8	18	Solid	1.85mm	0.66mm	6.45mm
9	18	Solid	1.85mm	0.66mm	6.93mm
10	18	Solid	1.85mm	0.66mm	7.52mm
12	18	Solid	1.85mm	0.66mm	7.75mm
13	18	Solid	1.85mm	0.66mm	8.18mm
16	18	Solid	1.85mm	0.66mm	8.61mm
19	18	Solid	1.85mm	0.66mm	9.07mm

Cable Printing:

*C/*AWG (UL) E481521 Underground Low Energy Circuit Cable 30V AC FOR LOW VOLTAGE OUTDOOR LIGHTING Direct Burial Sunlight Resistant RoHS ***FT

Listed:

