



Shenzhen Veisat Technology Co.,Ltd.

www.veisat.com

sell phone:+86 755 26013215

contact person:Ms Annie

mobile : +86 13434777602

Address:4F,6B,Changxing Industrial Zone, Changzhen, Gongming Park,Guangming District, shenzhen

Model	full hd OEM	Product Description	digital satellite tv receiver
Unit Price	USD7.5,FOB Shenzhen	MOQ: 2000PCS	size: mini
Weight	13.5kg/CTN/20PCS	CBM:0.051/CTN	iks account extral cost 0.4usd
Delivery Time	when the 30% deposit down,after 25 days finish the goods		
Terms of Payment	T/T ,all the balance down before shipment		
Quality Warranty	One year warranty		

Product Picture



Gift Box



FEATURE & SPECIFICATION

DVB-S2 HD FTA+2*USB PVR+BISS KEY+WIFI PROTOCOL,or choose other model

Specification:

- 1.DVB-S&DVB-S2 Compliant.
- 2.MPEG-2 MP@HL video decoder.
- 3.AVC/H.264 HP@L 4.1 video decoder.
- 4.MPEG4 ASP supported.
- 5.Fully compliant with HDMI1.3 specification.
- 6.Video
Resolution:1080p,1080i,720p,720i,576p,576i.
- 7.USB2.0 for PVR,Time-shift and timer.
- 8.Support MP3/WMA,AVI/MK/MP4...,BMP/JPG playback.
- 9.Blind scan,Sat scan,TP scan,NIT scan.
- 10.Max 2000 TP and 4000 Programs restore.
- 11.DiSEqc1.0/DiSEqc1.2/DiSEqc1.3(USALS).
- 12.Support 7-day EPG,Teletext and Subtitle.
- 13.Parental lock,Channel Edit,Favor edit.
- 14.OTA,RS232,USB upgrade.

Chipset and Memory

Processor:GX6605S/ ALI3510C / Sunplus1506G
Flash:32 serial flash
DDR:DDRII 800 512M
TUNER:AV2018

Power

Input:AC 90~270V,50/60 Hz
Operating:15W
Max:20W
Standby: ≤ 8W(Optional≤ 1W)

Interface

ANT IN x1,Audiox2,SPDIF digital output-
mini RCA,CVBSx1,Audiox2,SPDIF digital output
HDMI1.3x1
USB2.0 portx2 (only for USB disk)
RS232 mini

Video Decoding

Compliant with:MPEG-4 part10/MPEG-2 ISO/IEC 13818,
MPEG-4 Simple/Main/Advanced Profile @ Level(10 Mbps),
MPEG-2 Main Profile Main @ Level(15 Mbps),
H.264 MP @L L3(10 Mbps),H.264 HP @L4.1 (25 Mbps)
Video Resolution:1080p,1080i,720p,720i,576p,576i

Audio Decoding

Compliant with:MPEG-1/2/3,AC-3,KE AAC (optional)
Support Dolby down-mixed 2 channel (optional)

Physical

Dimensions (W x H x D) mini size
Weight:0.7
Temperature:0°C ~ +45°C
Humidity:8%~95%

Accessories: receiver*1pcs, user manual*1pcs, remote
contral*1pcs, RCA cable*1pcs,HDMI cable 50cm*1,battery*2pcs

