



| PIN数 | DIM=A | DIM=B | DIM=C | DIM=D |
|------|-------|-------|-------|-------|
| 30P | 35.2 | 29.00 | 37.0 | 31.10 |
| 29P | 34.2 | 28.00 | 36.0 | 30.10 |
| 28P | 33.2 | 27.00 | 35.0 | 29.10 |
| 27P | 32.2 | 26.00 | 34.0 | 28.10 |
| 26P | 31.2 | 25.00 | 33.0 | 27.10 |
| 25P | 30.2 | 24.00 | 32.0 | 26.10 |
| 24P | 29.2 | 23.00 | 31.0 | 25.10 |
| 23P | 28.2 | 22.00 | 30.0 | 24.10 |
| 22P | 27.2 | 21.00 | 29.0 | 23.10 |
| 21P | 26.2 | 20.00 | 28.0 | 22.10 |
| 20P | 25.2 | 19.00 | 27.0 | 21.10 |
| 19P | 24.2 | 18.00 | 26.0 | 20.10 |
| 18P | 23.2 | 17.00 | 25.0 | 19.10 |
| 17P | 22.2 | 16.00 | 24.0 | 18.10 |
| 16P | 21.2 | 15.00 | 23.0 | 17.10 |
| 15P | 20.2 | 14.00 | 22.0 | 16.10 |
| 14P | 19.2 | 13.00 | 21.0 | 15.10 |
| 13P | 18.2 | 12.00 | 20.0 | 14.10 |
| 12P | 17.2 | 11.00 | 19.0 | 13.10 |
| 11P | 16.2 | 10.00 | 18.0 | 12.10 |
| 10P | 15.2 | 9.00 | 17.0 | 11.10 |
| 9P | 14.2 | 8.00 | 16.0 | 10.10 |
| 8P | 13.2 | 7.00 | 15.0 | 9.10 |
| 7P | 12.2 | 6.00 | 14.0 | 8.10 |
| 6P | 11.2 | 5.00 | 13.0 | 7.10 |
| 5P | 10.2 | 4.00 | 12.0 | 6.10 |
| 4P | 9.2 | 3.00 | 11.0 | 5.10 |

| SER | AREA | REVISIONS | CHK | DATE |
|-----|------|-----------|-----|------|
| | | | | |
| | | | | |
| | | | | |
| | | | | |

UNLESS OTHERWISE SPECIFIED
 TOLERANCES ARE
 X.X ±0.15
 X.XX ±0.05
 X.XXX
 ANG. ±0°30'

| | | | |
|----------|-------|-------------|---|
| APPROVED | DATE | PART NO | 11-45-XX01-12 |
| CHECKED | DATE | DRAWING NO | JB96*08005 |
| DRAWN | DATE | COMPUTER NO | RD0800501 |
| NUMBER | SCALE | NAME | FPC 1.0 CONNECTOR H2.5 ZIF FOR SMT(SLIDE BOTTOM CONT) |
| 1/1 | 8:1 | SIZE | A3 |
| | | REV | A |

东莞市宽拓电子科技有限公司
Dongguan Kuantuo Electronics Co.,Ltd