

Single Side Ridging Making Machine

Tractor power: 50-100HP, Tractor Three-point Suspension + Hydraulic Output Joint.

Ridging height: 15-30cm, Top width: 27-37cm, bottom width: 62cm .

Transmission type: shaft drive + gear drive + chain drive.

Application range: paddy field and dry filed ridge, especially the terraced field ridge, Repair the canal and water the orchard.



Main machine main pictures.



Right rear side main pictures.



Rear side main pictures.



Model	ZGJ-350H
Name	Single side ridger making machine
Work speed	1200-2000 m/h
Configuration tractor	50-100HP Tractor
Transmission type	tractor PTO / shaft drive
on-link mode	After the tractor mounted
Height adjustment	After the tractor mounted / hydraulic cylinder adjust
Oil consumption	≤3kg/km
Overall size	Length 1300 mm
	Width 2100 mm
	Height 950 mm
Net weight	400 KG
Speed	240-280 r/min
Optimum operation conditions	The soil moisture content 20% - 60%

Three-point Suspension



Suspension type: same as like the tiller Suspension type, it's need to link to tractor hydraulic quick outlet.

Transmission Drive System



Gear box Transmission Part main picture (Figure 1)

Note: The gearbox has filling port and observation hole, which is convenient for users to fill gear oil and maintenance.



shaft drive part (Figure 2)

Transmission drive system: whole machine drive part is gear box drive and the chain drive, have the long work lift and lower failure rate.

Rotary Blade



Configuration the high quality and international standard rotary blade, convenient client order nearby.

Rolling Plate Material



Manganese steel(Higher hardness, low wear and tear and no soil).

Work effect pictures



Similar products used in paddy fields



Double side high speed ridger making machine for paddy field



Double disc gear box drive fertilizer spreader (500-2000L)