



Model	1GZ-120
Engine	Changhai 17/20KW/ 24/28HP
Gear box	(3F+1R) X2 high low speed
Climb angle	20 degree
Start type	Electric
Overall size	2300x1300x860 mm
Operation way	Hand and remote control
Net weight	700 KG
Wheel base	750 mm
Remote control distance	≥50 m
Distance ground	170 mm
Work speed	0.6-5.6km/h
Turning radius	1700 mm
Overall size (with till)	2300*1300*850 mm
Remote control distance	About 50 m
Pedrail	Standard Metal Track Customized Rubber Track
Attachment	Tiller, trencher, backfilling, mowing, fertilization, Spraying, crushing, transporting, ridging

Lawn mower

The high-speed vertical knife mower is suitable for cutting and crushing all kinds of weeds or weeds, leaving stubble flat.



Type	Vertical knife type
Work width	100-120 cm
Cutting height	3-5cm
Cutter shaft speed	2000r/minutes

Crawler garden ridger machine

The ridger is behind the rotary tiller to realize ridging while rotary tillage. It is suitable for intercropping sweet potatoes in orchards and greenhouse vegetable planting.



Height	20 cm
Bottom width	70 cm
Top width	40 cm

Crawler garden backfilling

Rotary tiller with split blade axle realizes backfilling operation function by replacing blade axle.



The cutter head of trencher is replaced with stirring dragon to realize backfilling operation. It is suitable for backfilling operation after trenching of positive plate trencher.



Type	Spiral Stirring Dragon
width	100-130 cm
Mixer speed	330 r/minutes

self propelled type wood shredder

Tractor Power Output and Variable Speed Structure Drive Tree Crusher



Type	Knife roller type
Shredder diameter	10 cm
Work effect	5 cbm /h
High feed port	96 cm
High discharge port	150 cm

self propelled fertilizer spreader

The combined operation of ditching, fertilization and mulching can adjust the amount of fertilization and the depth of fertilization. It is especially suitable for the fertilizer cloth operation of granular or powdery fertilizers.



Type	Ditching, Fertilizing and Covering Machine
Tank capacity	150L
Depth of fertilization	10-25 cm

Self-propelled trencher

Forward disc trencher

Suitable for opening ditches in non-cohesive soils in general soil orchards, with high efficiency and less residual at the bottom of ditches.



Swashplate trencher

Suitable for opening ditches in hard soil orchards on cohesive soil has high efficiency and less residual at the bottom of ditches.



Type	Forward disc	Swashplate
Trencher depth	30-35 cm	35 cm
Furrow top width	/	22 cm
Furrow bottom width	/	32 cm
Work effect	460-480 m/h	460-480 m/h
Cutter speed	330 r/minutes	330 r/minutes
Cutter diameter	63 cm	/

self propelled type garden air blast power sprayer

Good atomization, long spray distance; remote control operation, man-machine separation, operator safety.



Type	Air blast sprayer
Spray radius	6-7 m
Tank capacity	300 L
Overall size	250*120*100

self propelled type work platform

It is used not only to transport materials in the orchard, but also to transport fruits outside the orchard, so as to solve the problem of difficult transportation in the orchard



Type	Transporter platform
Ground distance	0.9m
Length	1.2m
Width	1m
Loading weight	500kg

Self-propelled rotary tiller

Remote control operation system, safe and convenient to use; compact structure, can be turned in situ; good pass, climbing ability, especially suitable for orchard, Dapeng and hills and other mechanized operations.



Type	Rotary, integral or split tool shafts
Work width	100-120 cm
Work depth	15-18 cm
Cutter speed	330 r/minutes