












浮球系列 Float Series



浮球系列 Float Series

Model 型号	Specification (mm) 规格(外径×高度×内径)	Material 材质	Weight 重量 (g)	Density 比重 (g/cm ³)	Temperature 使用温度	Pressure 耐压 (kg/cm ²)	Liquid 适用液体
FBP101	φ18×6.0×φ7.5	P.P.	0.9	0.70	-40 ~ +65℃	5	水 Water
FBP102	φ19×16.5×φ8.0	P.P.	2.8	0.73	-40 ~ +85℃	5	水 Water
FBP103	φ26×10×φ10	P.P.	3.2	0.73	-40 ~ +85℃	5	水 Water
FBP104	φ24×17×φ8.0	P.P.	4.0	0.62	-40 ~ +85℃	5	水 Water
FBP105	φ24×22×φ9.0	P.P.	5.0	0.60	-40 ~ +85℃	5	水 Water
FBP106	φ24×16.5×φ8.0	P.P.	4.2	0.65	-40 ~ +85℃	5	水 Water
FBP107	φ29×11×φ12	P.P.	4.4	0.72	-40 ~ +85℃	5	水 Water
FBP201	φ28×18.5×φ14	P.P.	4.8	0.74	-40 ~ +85℃	5	水 Water
FBPC01	47.5×21.5×10	P.P.	4.25	0.65	-40 ~ +85℃	5	水 Water
FBP501	φ26×26×φ9.5	P.P.	6.2	0.53	-40 ~ +110℃	8	水 Water
FBP502	φ25.6×16.8×φ9.2	P.P.	4.0	0.45	-40 ~ +110℃	8	水 Water
FBNL101	24.8×17×φ12.3	ny.lon	3.15	0.30	-40 ~ +65℃	8	水 Water
FBN101	φ25×15.5×φ10.5	NBR	3.8	0.56	-20 ~ +110℃	8	水、汽油、煤油 Water,oil
FBN102	φ25.5×15.5×φ10	NBR	3.7	0.55	-20 ~ +110℃	8	水、汽油、煤油 Water,oil
FBS101	φ24×24×φ9.5	SUS316	5.5	0.72	-40 ~ +200℃	8	水、油、弱酸、弱碱 Water,oil,weak acids and bases
FBS102	φ28×28×φ9.5	SUS316	8.4	0.70	-40 ~ +200℃	10	水、油、弱酸、弱碱 Water,oil,weak acids and bases
FBS103	φ45×56×φ15.5	SUS316	34.5	0.52	-40 ~ +200℃	15	水、油、弱酸、弱碱 Water,oil,weak acids and bases
FBS104	φ51×61×φ15.5	SUS316	37.0	0.42	-40 ~ +200℃	15	水、油、弱酸、弱碱 Water,oil,weak acids and bases
FBS105	φ51×51×φ15.5	SUS316	30.5	0.54	-40 ~ +200℃	15	水、油、弱酸、弱碱 Water,oil,weak acids and bases
FBS106	φ29.8×28×φ9.5	SUS316	18.5	0.70	-40 ~ +200℃	15	水、油、弱酸、弱碱 Water,oil,weak acids and bases
FBS107	φ40×35×φ15.5	SUS316	23.5	0.52	-40 ~ +200℃	15	水、油、弱酸、弱碱 Water,oil,weak acids and bases
FBS108	φ40.2×50.5×φ15.3	SUS316	28.5	0.52	-40 ~ +200℃	15	水、油、弱酸、弱碱 Water,oil,weak acids and bases

*Consult SOWAY for Customized Product 以上规格可按客户要求定制