



佳鉞有限公司

GOOPA LIMITED

香港青衣長達路 14-20 號, 偉力工業大廈 B 座 10/F 2 室  
Room 2, Block B 10/F, Vigor Industrial Building,  
14-20 Cheung Tat Road, Tsing Yi, N.T., Hong Kong  
Tel: 24314718, 24971998/24972198 Fax: (852)24971826  
<http://www.goopa.com.hk> e-mail: info@goopa.com.hk

## Amazing EcoGlue™



**Amazing EcoGlue™** one of the first Earth Friendly power glues with industrial strength designed for the do-it-yourselfer. EcoGlue is a water-based environmentally-safe glue that has less than 1% VOCs by weight and no animal derivatives or hazardous pollutants are found in this power glue. The bottle and card are 100% recyclable plastic and paper to keep the Earth Friendly promise to our consumers.

- **Bonding:** Amazing EcoGlue bonds with industrial strength to almost any material including wood, stone, metal, ceramic, glass, cloth and more!.
- **Non-toxic:** Water-based and 100% waterproof.
- **Use:** Environmentally safe interior/exterior glue.

**Find out more**

[How to Use Amazing EcoGlue](#)





**佳鉞有限公司**  
**GOOPA LIMITED**

香港青衣長達路 14-20 號, 偉力工業大廈 B 座 10/F 2 室  
Room 2, Block B 10/F, Vigor Industrial Building,  
14-20 Cheung Tat Road, Tsing Yi, N.T., Hong Kong  
Tel: 24314718, 24971998/24972198 Fax: (852)24971826  
<http://www.goopa.com.hk> e-mail: info@goopa.com.hk

## How To Use Amazing EcoGlue™

### Directions:

Follow these step-by-step directions when using Amazing EcoGlue:

1. Surface should be clean, dry and free from oil and grease.
2. Always test a small area first.
3. When bonding two surfaces, spread Amazing EcoGlue on both surfaces.
4. Initial bond in from 20-30 minutes. 3-6 hours for 80% strength. 24 hours for full strength. Water resistance reached within 3-5 days.
5. Clamping wood substrates is recommended when possible. Clamp for 20-60 minutes.
6. Application temperature is best between 60°F (16°C) to 100°F (38°C).
7. Heat resistant from 0 °F (-18°C) to 250°F (121°C) intermintently.