

| Turn | Rotor | B type winding | | | A type winding | | |
|-----------|-------|----------------|---------|-------|----------------|---------|-------|
| | | Resistance | Max Amp | RPM/V | Resistance | Max Amp | RPM/V |
| 2.5T | Φ12 | 0.0017 | 93 | 12877 | | | |
| | Φ12.5 | | | 12280 | | | |
| | Φ13 | | | 11420 | | | |
| | Φ13.5 | | | 10496 | | | |
| 3T | Φ12 | 0.0022 | 82 | | 0.0020 | 86 | |
| | Φ12.5 | | | 10148 | | | 9848 |
| | Φ13 | | | | | | |
| | Φ13.5 | | | | | | |
| 3.5T | Φ12 | 0.0027 | 75 | 9948 | 0.0026 | 76 | |
| | Φ12.5 | | | 9156 | | | |
| | Φ13 | | | 8449 | | | |
| | Φ13.5 | | | 7913 | | | 7749 |
| 4T | Φ12 | 0.0030 | 70 | | 0.0030 | 70 | |
| | Φ12.5 | | | 7851 | | | 7458 |
| | Φ13 | | | | | | |
| | Φ13.5 | | | | | | |
| 4.5T | Φ12 | 0.0048 | 56 | 8032 | 0.0042 | 59 | |
| | Φ12.5 | | | 7323 | | | 6958 |
| | Φ13 | | | 6838 | | | |
| | Φ13.5 | | | 6310 | | | |
| 5T (Δ) | Φ12 | 0.0022 | 82 | 12080 | | | |
| | Φ12.5 | | | 11218 | | | |
| | Φ13 | | | 10700 | | | |
| | Φ13.5 | | | 10140 | | | |
| 5.5T | Φ12 | 0.0064 | 48 | 6680 | | | |
| | Φ12.5 | | | 6069 | | | |
| | Φ13 | | | 5649 | | | |
| | Φ13.5 | | | 5214 | | | |
| 5.5T | Φ12.3 | | | | 0.0055 | 52 | 6368 |
| 6T (Δ) | Φ12 | 0.0026 | 76 | 10361 | 0.0024 | 79 | |
| | Φ12.5 | | | 9575 | | | 8971 |
| | Φ13 | | | 9008 | | | |
| | Φ13.5 | | | 8554 | | | |
| 6.5T | Φ12 | 0.0087 | 41 | 5645 | | | |
| | Φ12.3 | | | | | | |
| | Φ12.5 | | | 5157 | | | |
| | Φ13 | | | 4770 | | | |
| 6.5T | Φ13.5 | | | | 0.0070 | 46 | 5243 |
| 7T (Δ) | Φ12 | 0.0033 | 67 | 9200 | 0.0032 | 68 | |
| | Φ12.5 | | | 8154 | | | 7487 |
| | Φ13 | | | 7642 | | | |
| | Φ13.5 | | | 7184 | | | |
| 7.5T | Φ12 | 0.0104 | 38 | 5008 | | | |
| | Φ12.5 | | | 4534 | | | 4332 |
| | Φ13 | | | 4200 | | | |
| | Φ13.5 | | | 3918 | | | |

| Turn | Rotor | B type winding | | | A type winding | | |
|------------|-------|----------------|---------|-------|----------------|---------|-------|
| | | Resistance | Max Amp | RPM/V | Resistance | Max Amp | RPM/V |
| 8T (△) | Φ12 | 0.005 | 55 | | 0.0039 | 62 | 7246 |
| | Φ12.5 | | | 6875 | | | |
| | Φ13 | | | | | | |
| | Φ13.5 | | | | | | |
| 8.5T | Φ12 | 0.0142 | 32 | 4382 | | | |
| | Φ12.5 | | | 3983 | | | |
| | Φ13 | | | 3696 | | | |
| | Φ13.5 | | | 3449 | | | |
| 9T (△) | Φ12 | | | | 0.0046 | 57 | 6432 |
| | Φ12.5 | | | | | | |
| | Φ13 | | | | | | |
| | Φ13.5 | | | | | | |
| 9.5T | Φ12 | 0.0167 | 28 | 3950 | 0.0154 | 29 | 3504 |
| | Φ12.5 | | | 3610 | | | 3237 |
| | Φ13 | | | 3346 | | | |
| | Φ13.5 | | | 3106 | | | |
| 9.5T | Φ12.3 | | | | 0.0154 | 29 | 3648 |
| 10T (△) | Φ12 | 0.0064 | 48 | | | | |
| | Φ12.5 | | | 5863 | | | |
| | Φ13 | | | | | | |
| | Φ13.5 | | | | | | |
| 10.5T | Φ12 | 0.0213 | 24 | 3322 | | | |
| | Φ12.5 | | | 3254 | | | |
| | Φ13 | | | 3011 | | | |
| | Φ13.5 | | | 2842 | | | |
| 10.5T高温 | Φ12.5 | 0.0225 | 24 | 3254 | | | |
| 10.5T* | Φ12.3 | | | | 0.0167 | 26 | 3312 |
| 11.5T | Φ12 | 0.0258 | 23 | 3242 | | | |
| | Φ12.5 | | | 3002 | | | |
| | Φ13 | | | 2758 | | | |
| | Φ13.5 | | | 2566 | | | |
| 12T (△) | Φ12 | | | | 0.0082 | 40 | 4880 |
| | Φ12.5 | | | | | | |
| | Φ13 | | | | | | |
| | Φ13.5 | | | | | | |
| 12.5T | Φ12 | 0.0303 | 21 | 3092 | | | |
| | Φ12.5 | | | 2866 | | | |
| | Φ13 | | | 2676 | | | |
| | Φ13.5 | | | 2481 | | | |
| 13.5T | Φ12 | 0.0361 | 19 | 2773 | 0.0314 | 21 | 2471 |
| | Φ12.5 | | | 2592 | | | 2308 |
| | Φ13 | | | 2409 | | | |
| | Φ13.5 | | | 2229 | | | |
| 13.5T* | Φ12.3 | | | | 0.0277 | 21 | 2624 |
| 15.5T | Φ12 | 0.0415 | 18 | | | | |
| | Φ12.5 | | | 2108 | | | |
| | Φ13 | | | | | | |
| | Φ13.5 | | | | | | |

| Turn | Rotor | B type winding | | | A type winding | | |
|------------|-------|----------------|---------|-------|----------------|---------|-------|
| | | Resistance | Max Amp | RPM/V | Resistance | Max Amp | RPM/V |
| 17T (△) | Φ12 | | | | 0.0160 | 28 | 3443 |
| | Φ12.5 | | | | | | 3280 |
| | Φ13 | | | | | | 3110 |
| | Φ13.5 | | | | | | 2924 |
| 17.5T | Φ12 | 0.0514 | 16 | 1997 | 0.0492 | 16 | 1880 |
| | Φ12.5 | | | 1871 | | | 1760 |
| | Φ13 | | | | | | |
| | Φ13.5 | | | | | | |
| 17.5T | Φ12.3 | | | | 0.0469 | 16 | 2026 |
| 21.5T | Φ12 | 0.0875 | 12 | | | | |
| | Φ12.5 | | | 1565 | | | |
| | Φ13 | | | | | | |
| | Φ13.5 | | | | | | |
| 21.5T | Φ12.3 | 0.0875 | 12 | 1798 | | | |
| 23T (△) | Φ12 | 0.0339 | 20 | 2872 | | | |
| | Φ12.5 | | | 2700 | | | |
| | Φ13 | | | 2514 | | | |
| | Φ13.5 | | | 2363 | | | |
| 27T (△) | Φ12 | 0.0493 | 16 | 2390 | | | |
| | Φ12.5 | | | 2279 | | | |
| | Φ13 | | | 2139 | | | |
| | Φ13.5 | | | 2011 | | | |

Note: (△)means deta winding, *means the ROAR special windings, Without any mark means normal star windings