



Star Light Technology Group(China)Limited

Address 3&4/F Star Light Industry Building, Starlight Hi-Tech Park, Xixiang Town, Bao'an District, Shenzhen City PRC

Email karous@starlight-led.com Skype No. Karous.starlight www.starlight-led.com Tele: 86 135 1065 4911

T5Tube Specification

Integrated T5tube (Include single tube and shelf)



Applications

- ▣ Office Buildings
- ▣ Storage Facilities
- ▣ Retail Stores
- ▣ Supermarkets
- ▣ Residential
- ▣ Hotels
- ▣ Restaurants
- ▣ Warehouses
- ▣ Parking Lots
- ▣ Churches
- ▣ General Lighting
- ▣ Hospitals
- ▣ Shopping Malls
- ▣ Exhibition Halls



Item No.

Watts

International standard

2nd generation LED T5tube

100-125lum/W

Length and diameter (Include the shelf's length)

T5Tube-001B

6W

450*26*30mm

T5Tube-002B

9W

600*26*30mm

T5Tube-003B

15W

900*26*30mm

T5Tube-004B

18W

1200*26*30mm

T5Tube-005B

22W

1500*26*30mm

T5Tube-006B

24W

1500*26*30mm

T5Tube-007B

30W

1800*26*30mm

T5Tube-008B

40W

2400*26*30mm

Lighting Specification

LED Chip Type: SMD

Voltage Input: 100-277VAC

Light Efficacy:94.44 lm/W(FR)

Color Rendering Index (CRI):80

Available Color Temperatures

Technical Parameters

Dimmable : No


Beam Angel: 140°

Rated Life: 40,000+hours

Power factor:> 0.92

Driver Efficiency:> 90%

Total Harmonic Distortion(THD):12%



Can connect with each other between 2 integrated t5tubes as following photo

