



T5Tube Specification

Single T5tube (Only single tube **without shelf**)



Applications

- ▣ Office Buildings
- ▣ Storage Facilities
- ▣ Retail Stores
- ▣ Supermarkets
- ▣ Residential
- ▣ Hotels
- ▣ Restaurants
- ▣ Warehouses
- ▣ Parking Lots
- ▣ Churches
- ▣ General Lighting
- ▣ Hospitals
- ▣ Shopping Malls
- ▣ Exhibition Halls



Item No.

3rd generation LED T5tube

Watts

135-165lum/W

International standard

Length and diameter

- T5Tube-001A
- T5Tube-002A
- T5Tube-003A
- T5Tube-004A
- T5Tube-005A
- T5Tube-006A

- 9W
- 15W
- 18W
- 22W
- 24W
- 30W

- 550*Φ20mm Driver is inside the T5tube
- 850*Φ20mm Driver is inside the T5tube
- 1150*Φ20mm Driver is inside the T5tube
- 1150*Φ20mm Driver is inside the T5tube
- 1450*Φ20mm Driver is inside the T5tube
- 1450*Φ20mm Driver is inside the T5tube

Lighting Specification

LED Chip Type: SMD
 Voltage Input: 100-277VAC
 Light Efficacy:94.44 lm/W(FR)
 Color Rendering Index (CRI):80
 Available Color Temperatures

Technical Parameters

Dimmable : No
 Beam Angel: 140°
 Rated Life: 40,000+hours
 Power factor:> 0.92
 Driver Efficiency:> 90%
 Total Harmonic Distortion(THD):12%

